

# Package ‘rTensor2’

March 29, 2024

**Type** Package

**Title** MultiLinear Algebra

**Version** 2.0.0

**Maintainer** Kyle Caudle <kyle.caudle@sdsmt.edu>

**Description** A set of tools for basic tensor operators. A tensor in the context of data analysis in a multidimensional array. The tools in this package rely on using any discrete transformation (e.g. Fast Fourier Transform (FFT)). Standard tools included are the Eigenvalue decomposition of a tensor, the QR decomposition and LU decomposition. Other functionality includes the inverse of a tensor and the transpose of a symmetric tensor. Functionality in the package is outlined in Kernfeld et al. (2015) <<https://www.sciencedirect.com/science/article/pii/S0024379515004358>>.

**Depends** R (>= 4.2.0)

**Imports** methods,raster,png,rTensor, wavethresh, gsignal, Matrix,  
matrixcalc

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**LazyDataCompression** xz

**Config/testthat/edition** 3

**RoxygenNote** 7.2.3

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Kyle Caudle [aut, cre],  
Randy Hoover [ctb],  
Jackson Cates [ctb]

**Repository** CRAN

**Date/Publication** 2024-03-29 16:30:02 UTC

**R topics documented:**

as.tensor . . . . .	3
LU . . . . .	4
Mnist . . . . .	4
polar . . . . .	5
QR . . . . .	6
rand_tensor . . . . .	6
raytrace . . . . .	7
tDWT . . . . .	8
tEIG . . . . .	9
tEIGdct . . . . .	10
tEIGdht . . . . .	11
tEIGdst . . . . .	12
tEIGdwht . . . . .	12
tEIGdwt . . . . .	13
tEIGfft . . . . .	14
tIDWT . . . . .	15
tINV . . . . .	16
tINVdct . . . . .	17
tINVDht . . . . .	17
tINVdst . . . . .	18
tINVDwht . . . . .	19
tINVDwt . . . . .	19
tINVfft . . . . .	20
tLDA . . . . .	21
tLU . . . . .	22
tLUdct . . . . .	23
tLUdht . . . . .	24
tLUdst . . . . .	24
tLUdwht . . . . .	25
tLUDwt . . . . .	26
tLUfft . . . . .	26
tmean . . . . .	27
tmult . . . . .	28
tQR . . . . .	29
tQRdct . . . . .	30
tQRdht . . . . .	31
tQRdst . . . . .	31
tQRdwht . . . . .	32
tQRdwt . . . . .	33
tQRfft . . . . .	34
tSVD . . . . .	34
tSVDdct . . . . .	36
tSVDdht . . . . .	37
tSVDdst . . . . .	38
tSVDdwht . . . . .	39
tSVDdwt . . . . .	40

<code>as.tensor</code>	3
<code>tSVDfft</code> . . . . .	41
<code>t_tpose</code> . . . . .	42
<b>Index</b>	<b>43</b>

---

<code>as.tensor</code>	<i>Tensor Conversion</i>
------------------------	--------------------------

---

## Description

Create a [Tensor-class](#) object from an array, matrix, or vector.

## Usage

```
as.tensor(x, drop = FALSE)
```

## Arguments

- `x` : an instance of array, matrix, or vector
- `drop` : whether or not modes equal to 1 should be dropped

## Value

a [Tensor-class](#) object

## Author(s)

Kyle Caudle  
Randy Hoover  
Jackson Cates

## References

Imported from rTensor package version 1.4.8.

## Examples

```
#From vector
vec <- runif(3); vecT <- as.tensor(vec); vecT
#From matrix
mat <- matrix(runif(2*3),nrow=2,ncol=3)
matT <- as.tensor(mat); matT
#From array
indices <- c(2,3,4)
arr <- array(runif(prod(indices)), dim = indices)
arrT <- as.tensor(arr); arrT
```

---

LU

*LU Decomposition of a Complex Matrix*

---

**Description**

Decompose a square matrix A into the product of a lower triangular matrix L and an upper triangular matrix U.

**Usage**

LU(A)

**Arguments**

A : an  $n \times n$  matrix

**Value**

a lower triangular matrix L and an upper triangular matrix U so that  $A = LU$ .

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
z <- complex(real = rnorm(16), imag = rnorm(16))
A <- matrix(z,nrow=4)
LU(A)
```

---

Mnist

*Subset of MNIST training and testing data.*

---

**Description**

10000 MNIST training images (1000 of every digit), reformatted into a tensor: 28 x 10000 x 28.  
1000 MNIST test images (100 of every digit), reformatted into a tensor: 28 x 1000 x 28

**Usage**

data("Mnist")

**Format**

The format is:

Mnist\$train\$images, Mnist\$train\$labels

Mnist\$test\$images, Mnist\$test\$labels

**References**

Deng L (2012). “The mnist database of handwritten digit images for machine learning research.”  
IEEE Signal Processing Magazine, 29(6), 141–142

**Examples**

```
data(tensor)
```

---

polar

*Polar/Jordan Form of a Matrix*

---

**Description**

Creates the polar/Jordan form of the P and D matrices after performing eigenvalue decomposition where the eigenvalue values are complex.

**Usage**

```
polar(P,D)
```

**Arguments**

P : the eigenvectors from an eigenvalue decomposition.  
D : the eigenvalues from an eigenvalue decomposition.

**Value**

P the polar form (real-valued) matrix of eigenvectors.

D the polar form (real-valued) matrix of eigenvalues.

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
z <- complex(real = rnorm(16), imag = rnorm(16))  
M <- matrix(z,nrow=4)  
decomp <- eigen(M)  
polar(decomp$vectors,decomp$values)
```

---

QR *QR Decomposition of a Complex Matrix Without Pivoting*

---

**Description**

Performs QR Decomposition of a Complex Matrix without pivoting.

**Usage**

```
QR(A)
```

**Arguments**

A : an  $n \times n$  matrix

**Value**

an orthogonal matrix Q and an upper triangular matrix R so that  $A = QR$ .

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
z <- complex(real = rnorm(16), imag = rnorm(16))
A <- matrix(z, nrow=4)
QR(A)
```

---

rand\_tensor *Tensor with Random Entries*

---

**Description**

Generate a Tensor with specified modes with iid normal(0,1) entries.

**Usage**

```
rand_tensor(modes = c(3, 4, 5), drop = FALSE)
```

**Arguments**

modes : the modes of the output Tensor  
drop : whether or not modes equal to 1 should be dropped

**Value**

a Tensor object with modes given by modes

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**References**

Imported from rTensor package version 1.4.8.

**Examples**

```
rand_tensor()  
rand_tensor(c(4,4,4))  
rand_tensor(c(10,2,1),TRUE)
```

---

raytrace

*Subset of raytrace data*

---

**Description**

4 tensors (128 x 128 x 128) for 4 different gray scale images. boat, flashlight, keyboard, scooter.

**Usage**

```
data("raytrace")
```

**Format**

The format is:  
raytrace\$boat  
raytrace\$flashlight  
raytrace\$keyboard  
raytrace\$scooter

**References**

Hoover RC, Braman KS, Hao N (2011b). "Pose estimation from a single image using tensor decomposition and an algebra of circulants." In 2011 IEEE/RSJ International Conference on Intelligent Robots and Systems, pp. 2928–2934. IEEE.

**Examples**

```
data(raytrace)
```

---

`tDWT`*Discrete Wavelet Transform of a 3-D Tensor*

---

**Description**

Performs the Discrete Wavelet Transform of a 3-D Tensor.

**Usage**

```
tDWT(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**References**

G. Strang and T. Nguyen, Wavelets and filter banks. SIAM, 1996.

A. Haar, "Zur theorie der orthogonalen funktionensysteme", Mathematische annalen, vol. 69, no. 3, pp. 331-371, 1910.

**Examples**

```
T <- rand_tensor(modes=c(2,3,4))
print(tDWT(T))
```



tEIG

*Tensor Eigenvalue Decomposition Using any Discrete Transform***Description**

Performs a Eigenvalue decomposition of 3-mode tensor using any discrete transform.

**Usage**

```
tEIG(tnsr, tform)
```

**Arguments**

tnsr : a 3-mode tensor,  $n \times n \times k$   
 tform : Any discrete transform. Supported transforms are:  
 fft: Fast Fourier Transform  
 dwt: Discrete Wavelet Transform (Haar Wavelet)  
 dct: Discrete Cosine transform  
 dst: Discrete Sine transform  
 dht: Discrete Hadley transform  
 dwht: Discrete Walsh-Hadamard transform

**Value**

a [Tensor-class](#) object

If Eigenvalue decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

P: A tensor of Eigenvectors ( $n \times n \times k$ )

D: An diagonal tensor of Eigenvalues ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**References**

Kernfeld, E., Kilmer, M., & Aeron, S. (2015). Tensor-tensor products with invertible linear transforms. *Linear Algebra and its Applications*, 485, 545-570.

M. E. Kilmer, C. D. Martin, and L. Perrone, "A third-order generalization of the matrix svd as a product of third-order tensors," Tufts University, Department of Computer Science, Tech. Rep. TR-2008-4, 2008

K. Braman, "Third-order tensors as linear operators on a space of matrices", *Linear Algebra and its Applications*, vol. 433, no. 7, pp. 1241-1253, 2010.

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
tEIG(T,"dst")
```

---

tEIGdct	<i>Tensor Eigenvalue Decomposition Using the Discrete Cosine Transform</i>
---------	--

---

**Description**

Performs a Eigenvalue decomposition of 3-mode tensor using the discrete Cosine transform.

**Usage**

```
tEIGdct(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If Eigenvalue decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

P: A tensor of Eigenvectors ( $n \times n \times k$ )

D: An diagonal tensor of Eigenvalues ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tEIGdct(T))
```

---

tEIGdht	<i>Tensor Eigenvalue Decomposition Using the Discrete Hadley Transform</i>
---------	--

---

## Description

Performs a Eigenvalue decomposition of 3-mode tensor using the discrete Hadley transform.

## Usage

```
tEIGdht(tnsr)
```

## Arguments

tnsr : a 3-mode tensor

## Value

a [Tensor-class](#) object

If Eigenvalue decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

P: A tensor of Eigenvectors ( $n \times n \times k$ )

D: An diagonal tensor of Eigenvalues ( $n \times n \times k$ )

## Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

## Examples

```
T <- rand_tensor(modes=c(2,2,4))
print(tEIGdht(T))
```

---

tEIGdst

*Tensor Eigenvalue Decomposition Using the Discrete Sine Transform*


---

**Description**

Performs a Eigenvalue decomposition of 3-mode tensor using the discrete Sine transform.

**Usage**

```
tEIGdst(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If Eigenvalue decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

P: A tensor of Eigenvectors ( $n \times n \times k$ )

D: An diagonal tensor of Eigenvalues ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tEIGdst(T))
```

---

tEIGdwht

*Tensor Eigenvalue Decomposition Using the Discrete Walsh-Hadamard Transform*


---

**Description**

Performs a Eigenvalue decomposition of 3-mode tensor using the discrete Walsh-Hadamard transform.

**Usage**

```
tEIGdwt(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If Eigenvalue decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

P: A tensor of Eigenvectors ( $n \times n \times k$ )

D: An diagonal tensor of Eigenvalues ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tEIGdwt(T))
```

---

tEIGdwt	<i>Tensor Eigenvalue Decomposition Using the Discrete Wavelet Transform</i>
---------	---

---

**Description**

Performs a Eigenvalue decomposition of 3-mode tensor using the discrete Wavelet transform (Haar Wavelet).

**Usage**

```
tEIGdwt(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If Eigenvalue decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

P: A tensor of Eigenvectors ( $n \times n \times k$ )

D: An diagonal tensor of Eigenvalues ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**References**

G. Strang and T. Nguyen, Wavelets and filter banks. SIAM, 1996.

A. Haar, "Zur theorie der orthogonalen funktionensysteme," Mathematische annalen, vol. 69, no. 3, pp. 331–371, 1910.

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tEIGdwt(T))
```

---

tEIGfft

*Tensor Eigenvalue Decomposition Using the Discrete Fourier Transform*

---

**Description**

Performs a Eigenvalue decomposition of 3-mode tensor using the discrete Fourier transform.

**Usage**

```
tEIGfft(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If Eigenvalue decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

P: A tensor of Eigenvectors ( $n \times n \times k$ )

D: An diagonal tensor of Eigenvalues ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tEIGfft(T))
```

---

tIDWT

*Discrete Inverse Wavelet Transform of a 3-D Tensor*

---

**Description**

Performs the Discrete Inverse Wavelet Transform of a 3-D Tensor.

**Usage**

```
tIDWT(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**References**

G. Strang and T. Nguyen, Wavelets and filter banks. SIAM, 1996.  
A. Haar, "Zur theorie der orthogonalen funktionensysteme", Mathematische annalen, vol. 69, no. 3, pp. 331-371, 1910.

**Examples**

```
T <- rand_tensor(modes=c(2,3,4))  
print(tIDWT(T))
```

---

`tINV`*Inverse of a 3-mode Tensor Using any Discrete Transform*

---

**Description**

Performs the inverse of a tensor using the any discrete transform.

**Usage**

```
tINV(tnsr, tform)
```

**Arguments**

`tnsr` : a 3-mode tensor

`tform` : Any discrete transform. Supported transforms are:  
fft: Fast Fourier Transform  
dwt: Discrete Wavelet Transform (Haar Wavelet)  
dct: Discrete Cosine transform  
dst: Discrete Sine transform  
dht: Discrete Hadley transform  
dwht: Discrete Walsh-Hadamard transform

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tINV(T, "dst"))
```



---

`tINVdct`*Inverse of a 3-mode Tensor Using the Discrete Cosine Transform*

---

**Description**

Performs the inverse of a tensor using the discrete cosine transform.

**Usage**

```
tINVdct(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tINVdct(T))
```

---

`tINVdht`*Inverse of a 3-mode Tensor Using the Discrete Hartley Transform*

---

**Description**

Performs the inverse of a tensor using the discrete Hartley transform.

**Usage**

```
tINVdht(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tINVdht(T))
```

---

tINVdst

*Inverse of a 3-mode Tensor Using the Discrete Sine Transform*

---

**Description**

Performs the inverse of a tensor using the discrete sine transform.

**Usage**

```
tINVdst(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tINVdst(T))
```

---

tINVdwhT	<i>Inverse of a 3-mode Tensor Using the Discrete Walsh-Hadamard Transform</i>
----------	---

---

**Description**

Performs the inverse of a tensor using the discrete Walsh-Hadamard transform.

**Usage**

```
tINVdwhT(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tINVdwhT(T))
```

---

tINVdwt	<i>Inverse of a 3-mode Tensor Using the Discrete Wavelet Transform</i>
---------	--

---

**Description**

Performs the inverse of a tensor using the discrete wavelet transform (Haar Wavelet).

**Usage**

```
tINVdwt(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tINVdwt(T))
```

---

tINVfft

*Inverse of a 3-mode Tensor Using the Discrete Fourier Transform*

---

**Description**

Performs the inverse of a tensor using the discrete Fourier transform.

**Usage**

```
tINVfft(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tINVfft(T))
```

---

tLDA	<i>Linear Discriminate Analysis of a 3-mode Tensor Using any Discrete Transform</i>
------	---

---

**Description**

Performs linear discriminate analysis on a tensor using any discrete transform. Assumes tensor is sorted by classes.

**Usage**

```
tLDA(tnsr, nClass, nSamplesPerClass, tform)
```

**Arguments**

tnsr	: a 3-mode tensor
nClass	: Number of classes
nSamplesPerClass	: Samples in each class
tform	: one of six-discrete transforms. Supported transforms are: fft: Fast Fourier Transform dwt: Discrete Wavelet Transform (Haar Wavelet) dct: Discrete Cosine transform dst: Discrete Sine transform dht: Discrete Hadley transform dwht: Discrete Walsh-Hadamard transform

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
data("Mnist")
T <- Mnist$train$images
myorder <- order(Mnist$train$labels)
# tLDA need to be sorted by classes
T_sorted <- as.tensor(T[,myorder,])
# Using small tensor, 2 images for each class for demonstration
T <- T_sorted[,c(1:2, 1001:1002, 2001:2002, 3001:3002,
```

```

4001:4002,5001:5002,6001:6002,7001:7002,
8001:8002,9001:9002),]
tLDA(T,10,2,"dct")

```

---

tLU

---

*Tensor LU Decomposition Using Using Any Discrete Transform*


---

### Description

Performs a tensor LU decomposition on any 3-mode tensor using any discrete transform.

### Usage

```
tLU(tnsr, tform)
```

### Arguments

tnsr : a 3-mode tensor

tform : Any discrete transform. Supported transforms are:

- fft: Fast Fourier Transform
- dwt: Discrete Wavelet Transform (Haar Wavelet)
- dct: Discrete Cosine transform
- dst: Discrete Sine transform
- dht: Discrete Hadley transform
- dwht: Discrete Walsh-Hadamard transform

### Value

a [Tensor-class](#) object

If LU decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

L: The lower triangular tensor object ( $n \times n \times k$ )

U: The upper triangular tensor object ( $n \times n \times k$ )

### Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

## References

Kernfeld, E., Kilmer, M., & Aeron, S. (2015). Tensor-tensor products with invertible linear transforms. *Linear Algebra and its Applications*, 485, 545-570.

M. E. Kilmer, C. D. Martin, and L. Perrone, "A third-order generalization of the matrix svd as a product of third-order tensors," Tufts University, Department of Computer Science, Tech. Rep. TR-2008-4, 2008

K. Braman, "Third-order tensors as linear operators on a space of matrices", *Linear Algebra and its Applications*, vol. 433, no. 7, pp. 1241-1253, 2010.

## Examples

```
T <- rand_tensor(modes=c(2,2,4))
tLU(T,"dst")
```

---

tLUdct

---

*Tensor LU Decomposition Using the Discrete Cosine Transform*


---

## Description

Performs a LU decomposition of 3-mode tensor using the discrete Cosine transform.

## Usage

```
tLUdct(tnsr)
```

## Arguments

tnsr : a 3-mode tensor

## Value

a [Tensor-class](#) object

If LU decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

L: The lower triangular tensor object ( $n \times n \times k$ )

U: The upper triangular tensor object ( $n \times n \times k$ )

## Author(s)

Kyle Caudle [kyle.caudle@sdsmt.edu](mailto:kyle.caudle@sdsmt.edu)

## Examples

```
T <- rand_tensor(modes=c(2,2,4))
print(tLUdct(T))
```

---

`tLUdht`*Tensor LU Decomposition Using the Discrete Hartley Transform*

---

**Description**

Performs a LU decomposition of 3-mode tensor using the discrete Hartley transform.

**Usage**

```
tLUdht(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If LU decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

L: The lower triangular tensor object ( $n \times n \times k$ )

U: The upper triangular tensor object ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle [kyle.caudle@sdsmt.edu](mailto:kyle.caudle@sdsmt.edu)

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tLUdht(T))
```

---

`tLUdst`*Tensor LU Decomposition Using the Discrete Cosine Transform*

---

**Description**

Performs a LU decomposition of 3-mode tensor using the discrete Sine transform.

**Usage**

```
tLUdst(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor



**Value**

a [Tensor-class](#) object

If LU decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

L: The lower triangular tensor object ( $n \times n \times k$ )

U: The upper triangular tensor object ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle kyle.caudle@sdsmt.edu

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tLUdst(T))
```

---

tLUdwht

*Tensor LU Decomposition Using the Discrete Walsh-Hadamard Transform*

---

**Description**

Performs a LU decomposition of 3-mode tensor using the discrete Walsh-Hadamard transform.

**Usage**

```
tLUdwht(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If LU decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

L: The lower triangular tensor object ( $n \times n \times k$ )

U: The upper triangular tensor object ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle kyle.caudle@sdsmt.edu

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tLUdwht(T))
```

---

`tLUdwt`*Tensor LU Decomposition Using the Discrete Wavelet Transform*

---

**Description**

Performs a LU decomposition of 3-mode tensor using the discrete Wavelet transform (Haar Wavelet).

**Usage**

```
tLUdwt(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If LU decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

L: The left singular value tensor object ( $n \times n \times k$ )

U: The right singular value tensor object ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle [kyle.caudle@sdsmt.edu](mailto:kyle.caudle@sdsmt.edu)

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tLUdwt(T))
```

---

`tLUfft`*Tensor LU Decomposition Using the Discrete Fourier Transform*

---

**Description**

Performs a LU decomposition of 3-mode tensor using the discrete Fourier transform.

**Usage**

```
tLUfft(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If LU decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

L: The lower triangular tensor object ( $n \times n \times k$ )

U: The upper triangular tensor object ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle [kyle.caudle@sdsmt.edu](mailto:kyle.caudle@sdsmt.edu)

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tLUfft(T))
```

---

tmean	<i>Find the mean of a tensor</i>
-------	----------------------------------

---

**Description**

Find the mean of a 3-mode tensor.

**Usage**

```
tmean(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
tnsr <- rand_tensor(modes=c(3,4,5))
tmean(tnsr)
```

---

`tmult`*Tensor Multiplication Using Any Discrete Transform*

---

**Description**

Multiplies two 3-mode tensors using any discrete transform.

**Usage**

```
tmult(x,y,tform)
```

**Arguments**

`x` : a 3-mode tensor  
`y` : a 3-mode tensor  
`tform` : Any discrete transform. Supported transforms are:  
fft: Fast Fourier Transform  
dwt: Discrete Wavelet Transform (Haar Wavelet)  
dct: Discrete Cosine transform  
dst: Discrete Sine transform  
dht: Discrete Hadley transform  
dwht: Discrete Walsh-Hadamard transform

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T1 <- rand_tensor(modes=c(2,2,4))  
T2 <- rand_tensor(modes=c(2,3,4))  
print(tmult(T1,T2,"dst"))
```

---

`tQR`*Tensor QR Decomposition Using Any Discrete Transform*

---

**Description**

Performs a tensor QR decomposition on any 3-mode tensor using any discrete transform.

**Usage**

```
tQR(tnsr, tform)
```

**Arguments**

`tnsr` : a 3-mode tensor  
`tform` : Any discrete transform. Supported transforms are:  
fft: Fast Fourier Transform  
dwt: Discrete Wavelet Transform (Haar Wavelet)  
dct: Discrete Cosine transform  
dst: Discrete Sine transform  
dht: Discrete Hadley transform  
dwht: Discrete Walsh-Hadamard transform

**Value**

a [Tensor-class](#) object

If the QR decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

Q: The left singular value tensor object ( $n \times n \times k$ )

R: The right singular value tensor object ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle [kyle.caudle@sdsmt.edu](mailto:kyle.caudle@sdsmt.edu)

**References**

Kernfeld, E., Kilmer, M., & Aeron, S. (2015). Tensor-tensor products with invertible linear transforms. *Linear Algebra and its Applications*, 485, 545-570.

M. E. Kilmer, C. D. Martin, and L. Perrone, "A third-order generalization of the matrix svd as a product of third-order tensors," Tufts University, Department of Computer Science, Tech. Rep. TR-2008-4, 2008

K. Braman, "Third-order tensors as linear operators on a space of matrices", *Linear Algebra and its Applications*, vol. 433, no. 7, pp. 1241-1253, 2010.

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
tQR(T,"dst")
```

---

**tQRdct***Tensor QR Decomposition Using the Discrete Cosine Transform*

---

**Description**

Performs a QR decomposition of 3-mode tensor using the discrete Cosine transform.

**Usage**

```
tQRdct(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If QR decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

Q: An orthogonal tensor ( $n \times n \times k$ ).

R: An upper triangular tensor ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tQR(T,"dct"))
```

---

`tQRdht`*Tensor QR Decomposition Using the Discrete Hartley Transform*

---

**Description**

Performs a QR decomposition of 3-mode tensor using the discrete Hartley transform.

**Usage**

```
tQRdht(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If QR decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

Q: An orthogonal tensor ( $n \times n \times k$ ).

R: An upper triangular tensor ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tQRdht(T))
```

---

`tQRdst`*Tensor QR Decomposition Using the Discrete Sine Transform*

---

**Description**

Performs a QR decomposition of 3-mode tensor using the discrete Sine transform.

**Usage**

```
tQRdst(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If QR decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

Q: An orthogonal tensor ( $n \times n \times k$ ).

R: An upper triangular tensor ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tQRdst(T))
```

---

tQRdwht	<i>Tensor QR Decomposition Using the Discrete Walsh-Hadamard Transform</i>
---------	--

---

**Description**

Performs a QR decomposition of 3-mode tensor using the discrete Walsh-Hadamard transform.

**Usage**

```
tQRdwht(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If QR decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

Q: An orthogonal tensor ( $n \times n \times k$ ).

R: An upper triangular tensor ( $n \times n \times k$ )



**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tQRdwt(T))
```

---

tQRdwt

*Tensor QR Decomposition Using the Discrete Wavelet Transform*

---

**Description**

Performs a QR decomposition of 3-mode tensor using the discrete wavelet transform.

**Usage**

```
tQRdwt(tnsr)
```

**Arguments**

tnsr : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If QR decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

Q: An orthogonal tensor ( $n \times n \times k$ ).

R: An upper triangular tensor ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))  
print(tQRdwt(T))
```

---

`tQRfft`*Tensor QR Decomposition Using the Discrete Fourier Transform*

---

**Description**

Performs a QR decomposition of 3-mode tensor using the discrete Fourier transform.

**Usage**

```
tQRfft(tnsr)
```

**Arguments**

`tnsr` : a 3-mode tensor

**Value**

a [Tensor-class](#) object

If QR decomposition is performed on a  $n \times n \times k$  tensor, the components in the returned value are:

Q: An orthogonal tensor ( $n \times n \times k$ ).

R: An upper triangular tensor ( $n \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,2,4))
print(tQRfft(T))
```

---

`tSVD`*Tensor Singular Value Decomposition Using Any Discrete Transform*

---

**Description**

Performs a tensor singular value decomposition on any 3-mode tensor using any discrete transform.

**Usage**

```
tSVD(tnsr, tform)
```

**Arguments**

tnsr : a 3-mode tensor

tform : Any discrete transform. Supported transforms are:  
 fft: Fast Fourier Transform  
 dwt: Discrete Wavelet Transform (Haar Wavelet)  
 dct: Discrete Cosine transform  
 dst: Discrete Sine transform  
 dht: Discrete Hadley transform  
 dwht: Discrete Walsh-Hadamard transform

**Value**

a [Tensor-class](#) object

If the SVD is performed on a  $m \times n \times k$  tensor, the components in the returned value are:

U: The left singular value tensor object ( $m \times m \times k$ )

V: The right singular value tensor object ( $n \times n \times k$ )

S: A diagonal tensor ( $m \times n \times k$ )

**Author(s)**

Kyle Caudle

Randy Hoover

Jackson Cates

**References**

Kernfeld, E., Kilmer, M., & Aeron, S. (2015). Tensor-tensor products with invertible linear transforms. *Linear Algebra and its Applications*, 485, 545-570.

M. E. Kilmer, C. D. Martin, and L. Perrone, "A third-order generalization of the matrix svd as a product of third-order tensors," Tufts University, Department of Computer Science, Tech. Rep. TR-2008-4, 2008

K. Braman, "Third-order tensors as linear operators on a space of matrices", *Linear Algebra and its Applications*, vol. 433, no. 7, pp. 1241-1253, 2010.

**Examples**

```
T <- rand_tensor(modes=c(2,3,4))
print(tSVD(T, "dst"))
```

---

tSVDdct	<i>Tensor Singular Value Decomposition Using the Discrete Cosine Transform</i>
---------	--

---

### Description

Performs a tensor singular value decomposition on any 3-mode tensor using the discrete cosine transform.

### Usage

```
tSVDdct(tnsr)
```

### Arguments

tnsr : a 3-mode tensor

### Value

a [Tensor-class](#) object

If the SVD is performed on a  $m \times n \times k$  tensor, the components in the returned value are:

U: The left singular value tensor object ( $m \times m \times k$ )

V: The right singular value tensor object ( $n \times n \times k$ )

S: A diagonal tensor ( $m \times n \times k$ )

### Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

### Examples

```
T <- rand_tensor(modes=c(2,3,4))
print(tSVDdct(T))
```

---

tSVDdht	<i>Tensor Singular Value Decomposition Using the Discrete Harley Transform</i>
---------	--

---

### Description

Performs a tensor singular value decomposition on any 3-mode tensor using the discrete Harley transform.

### Usage

```
tSVDdht(tnsr)
```

### Arguments

tnsr : a 3-mode tensor

### Value

a [Tensor-class](#) object

If the SVD is performed on a  $m \times n \times k$  tensor, the components in the returned value are:

U: The left singular value tensor object ( $m \times m \times k$ )

V: The right singular value tensor object ( $n \times n \times k$ )

S: A diagonal tensor ( $m \times n \times k$ )

### Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

### Examples

```
T <- rand_tensor(modes=c(2,3,4))
print(tSVDdht(T))
```

---

tSVDdst	<i>Tensor Singular Value Decomposition Using the Discrete Sine Transform</i>
---------	--

---

### Description

Performs a tensor singular value decomposition on any 3-mode tensor using the discrete Sine transform.

### Usage

```
tSVDdst(tnsr)
```

### Arguments

tnsr : a 3-mode tensor

### Value

a [Tensor-class](#) object

If the SVD is performed on a  $m \times n \times k$  tensor, the components in the returned value are:

U: The left singular value tensor object ( $m \times m \times k$ )

V: The right singular value tensor object ( $n \times n \times k$ )

S: A diagonal tensor ( $m \times n \times k$ )

### Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

### Examples

```
T <- rand_tensor(modes=c(2,3,4))
print(tSVDdst(T))
```

---

tSVDdwht	<i>Tensor Singular Value Decomposition Using the Discrete Walsh-Hadamard Transform</i>
----------	--

---

### Description

Performs a tensor singular value decomposition on any 3-mode tensor using the discrete Walsh-Hadamard transform.

### Usage

```
tSVDdwht(tnsr)
```

### Arguments

tnsr : a 3-mode tensor

### Value

a [Tensor-class](#) object

If the SVD is performed on a  $m \times n \times k$  tensor, the components in the returned value are:

U: The left singular value tensor object ( $m \times m \times k$ )

V: The right singular value tensor object ( $n \times n \times k$ )

S: A diagonal tensor ( $m \times n \times k$ )

### Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

### Examples

```
T <- rand_tensor(modes=c(2,3,4))
print(tSVDdwht(T))
```

---

tSVDdwt	<i>Tensor Singular Value Decomposition Using the Discrete Wavelet Transform</i>
---------	---

---

### Description

Performs a tensor singular value decomposition on any 3-mode tensor using the discrete wavelet transform (Haar Wavelet).

### Usage

```
tSVDdwt(tnsr)
```

### Arguments

tnsr : a 3-mode tensor

### Value

a [Tensor-class](#) object

If the SVD is performed on a  $m \times n \times k$  tensor, the components in the returned value are:

U: The left singular value tensor object ( $m \times m \times k$ )

V: The right singular value tensor object ( $n \times n \times k$ )

S: A diagonal tensor ( $m \times n \times k$ )

### Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

### Examples

```
T <- rand_tensor(modes=c(2,3,4))
print(tSVDdwt(T))
```



---

tSVDfft	<i>Tensor Singular Value Decomposition Using the Discrete Fourier Transform</i>
---------	---

---

### Description

Performs a tensor singular value decomposition on any 3-mode tensor using the discrete Fourier transform.

### Usage

```
tSVDfft(tnsr)
```

### Arguments

tnsr : a 3-mode tensor

### Value

a [Tensor-class](#) object

If the SVD is performed on a  $m \times n \times k$  tensor, the components in the returned value are:

U: The left singular value tensor object ( $m \times m \times k$ )

V: The right singular value tensor object ( $n \times n \times k$ )

S: A diagonal tensor ( $m \times n \times k$ )

### Author(s)

Kyle Caudle

Randy Hoover

Jackson Cates

### Examples

```
T <- rand_tensor(modes=c(2,3,4))  
print(tSVDfft(T))
```

---

`t_tpose`*Transpose 3-mode Tensor*

---

**Description**

Performs the transpose of a symmetric 3-mode tensor using any discrete transform.

**Usage**

```
t_tpose(tnsr, tform)
```

**Arguments**

`tnsr` : a 3-mode tensor  
`tform` : Any discrete transform. Supported transforms are:  
fft: Fast Fourier Transform  
dwt: Discrete Wavelet Transform (Haar Wavelet)  
dct: Discrete Cosine transform  
dst: Discrete Sine transform  
dht: Discrete Hadley transform  
dwht: Discrete Walsh-Hadamard transform

**Value**

a [Tensor-class](#) object

**Author(s)**

Kyle Caudle  
Randy Hoover  
Jackson Cates

**Examples**

```
T <- rand_tensor(modes=c(2,3,4))  
print(t_tpose(T,"dct"))
```

# Index

- \* **datasets**
  - Mnist, 4
  - raytrace, 7
- \* **misc**
  - LU, 4
- as.tensor, 3
- LU, 4
- Mnist, 4
- polar, 5
- QR, 6
- rand\_tensor, 6
- raytrace, 7
- t\_tpose, 42
- tDWT, 8
- tEIG, 9
- tEIGdct, 10
- tEIGdht, 11
- tEIGdst, 12
- tEIGdwht, 12
- tEIGdwt, 13
- tEIGfft, 14
- tIDWT, 15
- tINV, 16
- tINVdct, 17
- tINVdht, 17
- tINVdst, 18
- tINVdwht, 19
- tINVdwt, 19
- tINVfft, 20
- tLDA, 21
- tLU, 22
- tLUdct, 23
- tLUdht, 24
- tLUdst, 24
- tLUdwht, 25
- tLUdwt, 26
- tLUfft, 26
- tmean, 27
- tmult, 28
- tQR, 29
- tQRdct, 30
- tQRdht, 31
- tQRdst, 31
- tQRdwht, 32
- tQRdwt, 33
- tQRfft, 34
- tSVD, 34
- tSVDdct, 36
- tSVDdht, 37
- tSVDdst, 38
- tSVDdwht, 39
- tSVDdwt, 40
- tSVDfft, 41