

Package ‘supervisedPRIM’

October 14, 2022

Title Supervised Classification Learning and Prediction using Patient Rule Induction Method (PRIM)

Version 2.0.0

Date 2016-10-01

Description The Patient Rule Induction Method (PRIM) is typically used for “bump hunting” data mining to identify regions with abnormally high concentrations of data with large or small values. This package extends this methodology so that it can be applied to binary classification problems and used for prediction.

Depends R ($\geq 3.1.1$), stats, prim ($\geq 1.0.16$)

Suggests kernlab, testthat

License GPL-3

URL <https://github.com/dashaub/supervisedPRIM>

BugReports <https://github.com/dashaub/supervisedPRIM/issues>

LazyData true

RoxygenNote 5.0.1

ByteCompile true

NeedsCompilation no

Author David Shaub [aut, cre]

Maintainer David Shaub <davidshaub@gmx.com>

Repository CRAN

Date/Publication 2016-10-01 14:39:25

R topics documented:

predict.supervisedPRIM	2
supervisedPRIM	2
Index	4

```
predict.supervisedPRIM
```

Model Predictions

Description

Perform prediction on a trained supervisedPRIM model. Output to either predicted class or positive class probability is supported.

Usage

```
## S3 method for class 'supervisedPRIM'
predict(object, newdata, classProb = FALSE, ...)
```

Arguments

object	A trained model of class supervisedPRIM returned by supervisedPRIM
newdata	The new data on which to create predictions
classProb	Should the function return the estimated class
...	additional arguments (ignored) probabilities instead of the predicted class?

Author(s)

David Shaub

Examples

```
# Train a model to determine if a flower is setosa
data(iris)
yData <- factor(ifelse(iris$Species == "setosa", "setosa", "other"), levels = c("setosa", "other"))
xData <- iris
xData$Species <- NULL
primModel <- supervisedPRIM(x = xData, y = yData)
# Predict on the original dataset
predictions <- predict(primModel, newdata = xData)
```

```
supervisedPRIM
```

Fit PRIM model to a labeled dataset

Description

perform supervised classification using Patient Rule Induction Method (PRIM)

Usage

```
supervisedPRIM(x, y, peel.alpha = 0.05, paste.alpha = 0.01,
  mass.min = 0.05, threshold.type = 1, ...)
```

Arguments

<code>x</code>	matrix of data values
<code>y</code>	binary vector of 0/1 response values
<code>peel.alpha</code>	peeling quantile tuning parameter
<code>paste.alpha</code>	pasting quantile tuning parameter
<code>mass.min</code>	minimum mass tuning parameter
<code>threshold.type</code>	threshold direction indicator: 1 = " \geq threshold", -1 = " \leq threshold"
<code>...</code>	additional arguments to pass to prim.box

Details

Fit

Value

an object of class `supervisedPRIM`. See additional details in [prim.box](#)

Author(s)

David Shaub

Examples

```
# Train a model to determine if a flower is setosa
data(iris)
yData <- factor(ifelse(iris$Species == "setosa", "setosa", "other"), levels = c("setosa", "other"))
xData <- iris
xData$Species <- NULL
primModel <- supervisedPRIM(x = xData, y = yData)
```

Index

`predict.supervisedPRIM`, 2

`prim.box`, 3

`supervisedPRIM`, 2, 2