

Package ‘verbalisr’

September 3, 2024

Type Package

Title Describe Pedigree Relationships in Words

Version 0.7.1

Description Describe in words the genealogical relationship between two members of a given pedigree, using the algorithm in Vigeland (2022) [doi:10.1186/s12859-022-04759-y](https://doi.org/10.1186/s12859-022-04759-y). 'verbalisr' is part of the 'pedsuite' collection of packages for pedigree analysis. For a demonstration of 'verbalisr', see the online app 'QuickPed' at <https://magnusdv.shinyapps.io/quickped/>.

License GPL-3

URL <https://github.com/magnusdv/verbalisr>,
<https://magnusdv.github.io/pedsuite/>

BugReports <https://github.com/magnusdv/verbalisr/issues>

Depends pedtools (>= 2.2.0), R (>= 4.1)

Imports ribd (>= 1.6.1)

Suggests testthat

Encoding UTF-8

Language en-GB

LazyData true

RoxygenNote 7.3.2

NeedsCompilation no

Author Magnus Dehli Vigeland [aut, cre]
(<https://orcid.org/0000-0002-9134-4962>)

Maintainer Magnus Dehli Vigeland <m.d.vigeland@medisin.uio.no>

Repository CRAN

Date/Publication 2024-09-03 03:40:02 UTC

Contents

habsburg	2
print.pairrel	2
verbalise	3
Index	5

habsburg	<i>Habsburg pedigree.</i>
----------	---------------------------

Description

A subset of the royal Habsburg family, showing the ancestry of (the infamously inbred) King Charles II of Spain.

Usage

```
habsburg
```

Format

A ped object containing a pedigree with 29 members.

Source

Adapted from https://en.wikipedia.org/wiki/Habsburg_family_tree

Examples

```
plot(habsburg, hatched = "Charles II", cex = 0.7)
verbalise(habsburg, ids = parents(habsburg, "Charles II"))
```

print.pairrel	<i>Format and print relationship descriptions</i>
---------------	---

Description

This documents the options for formatting and printing the output of `verbalise()`.

Usage

```
## S3 method for class 'pairrel'
print(x, ...)

## S3 method for class 'pairrel'
format(
  x,
  cap = TRUE,
  simplify = FALSE,
  abbreviate = FALSE,
  collapse = NULL,
  includePaths = !simplify,
  ...
)
```

Arguments

x	An output of <code>verbalise()</code> .
...	Arguments passed on to <code>format.pairrel()</code> .
cap	A logical indicating if the first letter of each path description should be capitalised. By default TRUE.
simplify	A logical. If TRUE, the descriptions of lineal and avuncular relationships are simplified. Default: FALSE.
abbreviate	A logical. If TRUE, various abbreviations are applied to the descriptions, e.g. 'great-great' -> 'gg-' and 'once removed' -> '1r'. Default: FALSE.
collapse	A single string, or NULL. If given, and the relationship has multiple descriptions, these are concatenated with <code>paste(..., collapse = collapse)</code> .
includePaths	A logical indicating if the complete paths should be included in the output. By default TRUE.

 verbalise

Describe a pairwise relationship

Description

The description includes all pedigree paths between the two individuals, indicating with brackets the topmost common ancestors in each path. See `print.pairrel()` for formatting options when printing the results.

Usage

```
verbalise(x, ids = leaves(x))
```

Arguments

`x` A ped object, or a list of such.
`ids` A vector containing the names of two pedigree members.

Value

An object of class `pairrel`. This is essentially a list of lists, containing many details about each path between the individuals. Most users will not interact with this list directly, but simply use the description provided by the `print()` method.

See Also

[print.pairrel\(\)](#).

Examples

```
# Example 1: Family quartet

x = nuclearPed(2)
verbalise(x, 1:2)
verbalise(x, 2:3)
verbalise(x, 3:4)

# Simplified output
verbalise(x, 2:3) |> print(simplify = TRUE)

# Example 2: Complicated cousin pedigree

y = doubleCousins(degree1 = 1, removal1 = 1, half1 = TRUE,
                  degree2 = 2, removal2 = 0, half2 = FALSE)
verbalise(y)

# Example 3: Full sib mating

z = fullSibMating(1)
verbalise(z)
verbalise(z, ids = c(1,5))
verbalise(z, ids = c(1,5)) |> print(simplify = TRUE)

# Example 4: Quad half first cousins

w = quadHalfFirstCousins()
verbalise(w)
```

Index

* datasets

habsburg, [2](#)

`format.pairrel (print.pairrel)`, [2](#)

habsburg, [2](#)

`print.pairrel`, [2](#)

`print.pairrel()`, [3](#), [4](#)

verbalise, [3](#)

`verbalise()`, [2](#), [3](#)