

secrdesign - sampling design for spatially explicit capture–recapture

Murray Efford

2017-12-04

Contents

Introduction	2
A simple example	3
Defining scenarios	4
Detector layouts	4
The scenarios dataframe	5
Running simulations	6
Arguments of <code>run.scenarios()</code>	6
Customising <code>run.scenarios()</code>	7
More on masks	8
Summarising simulation output	9
Extracting estimate tables from fitted models	9
Choosing the statistics to summarise	9
Disposing of rogue values	11
Summary method	12
Plot method	14
Additional topics	15
Parallel processing	15
Shortcut evaluation of precision	16
Non-uniform populations	17
Linear habitat	18
Splitting data generation and model fitting	18
Populations with sub-classes or multiple sessions	21
Limitations, tips and troubleshooting	22
References	22
Appendix 1. Default <code>extractfn</code> for <code>run.scenarios</code>.	24
Appendix 2. Examples	25
Multiple grids, varying number of occasions	25
Learned trap response	28
Non-uniform possums	33
Code for linear habitat	36
Grouped populations	39

The R package **secrdesign** is a set of tools to assist the design of studies using spatially explicit capture–recapture (SECR). It provides convenient wrappers for simulation and model fitting functions in package **secr** to emulate many features of the ‘Simulator’ module of Density 5.0 (Efford 2012).

This document is a technical guide to the simulation aspects of **secrdesign**. Functions that do not rely on simulation are described in `secrdesign-tools.pdf`.

We assume an understanding of estimator properties such as bias, precision, and confidence interval coverage, and the use of Monte Carlo simulation to predict the performance of different sampling designs. Using **secrdesign** can be daunting because it allows for many different combinations of data generation, model fitting and summary statistics. Several examples are given to indicate the range of possibilities.

Introduction

When designing a study you should have in mind –

- (i) a population parameter you want to measure (probably density or population size),
- (ii) one or more design variables over which you have some control (number and spacing of detectors, number of sampling occasions etc.),
- (iii) some pilot data, or parameter estimates from published studies, and
- (iv) a criterion by which to evaluate different designs. This is most likely the precision of the estimates, as this in turn determines your ability (power) to recognise changes. Cost or effort may be an explicit criterion, or the designs may be constructed to allocate constant effort in different ways.

We use ‘relative standard error’ (RSE) for the relative precision of an estimate. This is sometimes called the coefficient of variation (CV) of the estimate, but RSE is more appropriate. We use ‘accuracy’ in the sense of Williams et al. (2002 p.45) and other authors from the United States. Accuracy combines both systematic error (bias) and precision: one measure is the square root of the mean squared difference between the true value and the estimate (RMSE).

Once you have sorted out (i)–(iv) you are ready to define and compare sampling scenarios. Scenarios are specified in a dataframe that is usually constructed with `make.scenarios` (see The scenarios dataframe). Each scenario has an integer ‘trapsindex’ code that identifies a particular detector array; a list of detector arrays is constructed separately, possibly using functions such as `make.grid`.

Scenarios may be investigated in two ways –

- tabulation of expected counts etc. with `scenarioSummary`
- Monte Carlo simulation with `run.scenarios`.

Monte Carlo simulation is ultimately the more reliable and comprehensive route, but it is much slower.

Fig. 1 shows the sequence of steps taken in **secrdesign** to conduct simulations and summarise the results. Each step is described in detail in a later section. Typically, you will use `run.scenarios()` to generate data and fit SECR models, select some statistics with `select.stats()`, and summarise and plot the results.




Fig. 1. Core functions in **secrdesign** (yellow) and their main inputs and outputs. Output from the simulation function **run.scenarios()** may be saved as whole fitted models, predicted values (parameter estimates), or selected statistics. Each form of output requires different subsequent handling. The default path is shown by solid blue arrows.

A simple example

For an introductory example we construct a simple set of scenarios and perform some simulations. The trap layout is a default 6 x 6 grid of multi-catch traps at 20-m spacing. Density takes one of two levels (5/ha or 10/ha) and detection parameters sigma and lambda0 are fixed.

```
library(secrdesign)
```

```
## Loading required package: secr
```

```
## This is secr 3.1.2. For overview type ?secr
```

```
## This is secrdesign 2.5.3. For overview type ?secrdesign
```

```
scen1 <- make.scenarios(D = c(5,10), sigma = 25, g0 = 0.2)
```

```
traps1 <- make.grid(8, 8, spacing = 25)
```

```
scenarioSummary(scen1, traps1)
```

```
##   scenario trapsindex noccasions nrepeats  D  g0 sigma detectfn    En    Er    Em
## 1         1          1           3         1  5 0.2   25         0 27.652 22.453 19.601
## 2         2          1           3         1 10 0.2   25         0 55.303 44.905 39.203
##          esa CF rotRSE rotRSEB arrayN arrayspace arrayspan saturation
```

```
## 1 5.530333 1 0.2110 0.1714 64 1 9.8995 0.2369281
## 2 5.530333 1 0.1492 0.1212 64 1 9.8995 0.4172652
```

The initial summary includes the expected number of individuals (En) and recaptures (Er), and an approximate rule-of-thumb relative standard error for estimated density (rotRSE). `scenarioSummary` approximates the default detection function (HN) by a hazard-based detection function (HHN) with a warning that is not shown here. See `?scenarioSummary` and `secdesign-tools.pdf` for further details.

```
sims1 <- run.scenarios(nrepl = 50, trapset = traps1, scenarios =
  scen1, seed = 345, fit = TRUE, fit.args = list(detectfn = 'HHN'))
```

```
## Completed scenario 1
```

```
## Completed scenario 2
```

```
## Completed in 3.171 minutes
```

The simulation output is an object of class `c("estimatetables", "secdesign", "list")`. We use the summary method for `estimatetables` to view results, and here display only the summary output (omitting a header that describes the simulations).

```
summary(sims1)$OUTPUT
```

```
## $`1`
##           n      mean      se
## estimate  50  5.02808 0.15602
## SE.estimate 50  1.05707 0.01865
## lcl       50  3.35008 0.12476
## ucl       50  7.56696 0.18881
## RB        50  0.00562 0.03120
## RSE       50  0.21583 0.00426
## COV       50  0.98000 0.02000
##
## $`2`
##           n      mean      se
## estimate  50  9.86995 0.20303
## SE.estimate 50  1.47010 0.01856
## lcl       50  7.38442 0.17085
## ucl       50 13.19702 0.23887
## RB        50 -0.01301 0.02030
## RSE       50  0.15023 0.00142
## COV       50  0.96000 0.02799
```

In this example there is close agreement between the fast rule-of-thumb RSE and the simulation results.

Later sections show how to customize the summary and plot results.

Defining scenarios

Detector layouts

Detector layouts are specified as `secdesign` ‘traps’ objects. These may be input from text files using `read.traps` or constructed according to a particular geometry and spacing with functions such as `make.grid`, `make.circle`, `make.systematic` or `trap.builder`. See the help files for these `secdesign` functions for further details. The detector type (multi-catch trap, proximity detector etc.) is stored as an attribute of each ‘traps’ object, which may also include detector-level covariates and detector ‘usage’ by occasion.

Multiple layouts are combined in a single list object; component names ('grid6x6' etc.) will be used to annotate the output.

```
library(secrdesign)

## Warning: package 'secrdesign' was built under R version 3.4.3
## Loading required package: secr
## This is secr 3.1.3. For overview type ?secr
## This is secrdesign 2.5.3. For overview type ?secrdesign
mydetectors <- list(grid6x6 = make.grid(6,6),
                    grid8x9 = make.grid(8,9),
                    grid12x12 = make.grid(12,12))
```

This creates square grids with the default detector type 'multi' and default spacing 20 m. See `?secr::make.grid` for other options.

The scenarios dataframe

The function `make.scenarios()` constructs a dataframe in which each row defines a simulation scenario. Its arguments (with defaults) are:

```
make.scenarios (trapsindex = 1, nooccasions = 3, nrepeats = 1, D, g0,
                sigma, lambda0, detectfn = 0, recapfactor = 1, popindex = 1,
                detindex = 1, fitindex = 1, groups, crosstraps = TRUE)
```

Each argument except for 'groups' and 'crosstraps' may be used to specify a range of values for a parameter. Four ('trapsindex', 'popindex', 'detindex', 'fitindex') are actually surrogate numerical indices; the index is used to select one component from a list of possibilities later provided as input to `run.scenarios()`.

By default, a scenario is formed from each unique combination of the input values (trapsindex, nooccasions, nrepeats, D, g0, sigma, lambda0, detectfn, recapfactor, popindex, and fitindex) using `expand.grid`. For example,

```
make.scenarios (trapsindex = 1:3, nooccasions = 4, D = 5, g0 = 0.2, sigma = c(20,30))
```

##	scenario	trapsindex	nooccasions	nrepeats	D	g0	sigma	detectfn	recapfactor	popindex
## 1	1	1	4	1	5	0.2	20	0	1	1
## 2	2	2	4	1	5	0.2	20	0	1	1
## 3	3	3	4	1	5	0.2	20	0	1	1
## 4	4	1	4	1	5	0.2	30	0	1	1
## 5	5	2	4	1	5	0.2	30	0	1	1
## 6	6	3	4	1	5	0.2	30	0	1	1
##	detindex	fitindex								
## 1	1	1								
## 2	1	1								
## 3	1	1								
## 4	1	1								
## 5	1	1								
## 6	1	1								

In this case three different grids (possibly differing in number of traps) are trapped for the same number of occasions. A more interesting possibility is to vary the number of occasions inversely with the number of traps. However, if we naively set e.g., `nooccasions = c(8, 4, 2)`, this would generate all combinations of grid and number of occasions (18 different scenarios).

The alternative is to set `crosstraps = FALSE`. Then the vectors ‘trapsindex’, ‘noccasions’, and ‘nrepeats’ are locked together (if fewer values are provided in one of the vectors then it is re-used as required), and only the combination is crossed with the remaining parameter scenarios:

```
make.scenarios (trapsindex = 1:3, noccasions = c(8,4,2), D = 5, g0 = 0.2,
               sigma = c(20,30), crosstraps = FALSE)
```

```
## scenario trapsindex noccasions nrepeats D g0 sigma detectfn recapfactor popindex
## 1 1 1 8 1 5 0.2 20 0 1 1
## 2 2 2 4 1 5 0.2 20 0 1 1
## 3 3 3 2 1 5 0.2 20 0 1 1
## 4 4 1 8 1 5 0.2 30 0 1 1
## 5 5 2 4 1 5 0.2 30 0 1 1
## 6 6 3 2 1 5 0.2 30 0 1 1
## detindex fitindex
## 1 1 1
## 2 1 1
## 3 1 1
## 4 1 1
## 5 1 1
## 6 1 1
```

All arguments except ‘fitindex’ control the generation of data. Note that ‘g0’ and ‘lambda0’ are alternatives: use the one appropriate to the detection function specified with `detectfn` (see `?secre::detectfn` for codes). ‘D’ is omitted if an inhomogeneous Poisson distribution is specified using a mask covariate (see Non-uniform populations). D is in animals / hectare (1 ha = 0.01km²) and sigma is in metres, as in `secre`.

The ‘nrepeats’ column refers to the number of notional independent replicates of the particular detector layout. Notional replicates are simulated by (invisibly) multiplying density (D) by this factor, and ultimately dividing it into the estimate. Think of 5 grids of automatic cameras so widely separated that no animal moves between the grids. As detections of different animals are ordinarily modelled as independent, the entire design is equivalent to 5 times the density of animals interacting with one grid. This breaks down, of course, if animals compete for traps (as with single-catch traps), and should not be used in that case except as a rough approximation.

Just as `trapsindex` serves as a placeholder for entire detector arrays, `popindex`, `detindex` and `fitindex` tell `run.scenarios()` which set of arguments to select from `pop.args`, `det.args` and `fit.args` for `sim.popn`, `sim.capthist` and `secre.fit` respectively. These are for more advanced use: you may not need them.

When a vector of group identifiers is provided in ‘groups’, the population in each scenario is a set of independently sampled groups, each defined on a separate row. Groups are initially assigned the same parameter values and other settings: it is up to the user to insert group-specific values (example at Grouped populations).

Running simulations

The function `run.scenarios()` generates multiple datasets and, if requested, fits an SECR model to each one. In this section we describe its main arguments, with additional detail on habitat masks and customizing the output.

Arguments of `run.scenarios()`

```
run.scenarios (nrepl, scenarios, trapset, maskset, xsigma = 4,
              nx = 32, pop.args, det.args, fit = FALSE, fit.args, chatnsim = 0,
```

```
extractfn = NULL, multisession = FALSE, ncores = 1, byscenario = TRUE,
seed = 123)
```

`nrepl` determines the number of replicate simulations. Make this large enough that the summary statistics have enough precision to answer your question. This is usually a matter for experimentation, remembering that precision (SE) is proportional to the square root of `nrepl`.

`scenarios` is the dataframe constructed with `make.scenarios()` as described in the last section.

`trapset` is a single ‘traps’ object or a list of traps objects, as described in ‘Detector layouts’ above.

`maskset` is an optional set of habitat masks, usually one per detector layout. If not specified, then masks will be constructed ‘on the fly’ using `secr::make.mask` with a ‘buffer’ of width $x\sigma \times \text{scenarios}\$sigma$ and `nx` cells in the x dimension.

`pop.args` provides additional control over `sim.popn` (see `?secr::sim.popn` for more). You may wish, for example, to set `pop.args = list(Ndist = "fixed")` to override the default of Poisson variation in the total number of simulated animals.

`det.args` provides additional control over `sim.caphist` (see `?secr::sim.caphist` for more). One use is to retain the simulated population as an attribute of the caphist object by setting `det.args = list(savepopn = TRUE)`; another is to set the `binomN` argument for count detectors. The `sim.caphist` arguments `traps`, `popn`, `detectpar`, `detectfn` and `noccasions` are defined in the scenario or `pop.args` and cannot be overridden by setting `det.args`.

Use `fit = FALSE` to generate and summarise detection data without fitting SECR models. This lets you check that your scenarios result in reasonable numbers of detected individuals (`n`), detections (`ndet`), and movements (`nmov`), before launching a full-blown simulation.

`fit.args` lets you specify how SECR models will be fitted to the simulated data. Most default arguments of `secr.fit` may be overridden by including them in `fit.args`. For example, to specify a negative exponential detection function use `fit.args = list(detectfn = "EX")`. If you wish to compare `nspec` different model specifications then `fit.args` should be a list of lists, one per specification, with `fitindex` taking values in the range 1:`nspec`.

The use of `multisession`, `ncores` and `byscenario` is discussed under Additional topics.

Customising `run.scenarios()`

The output from `run.scenarios()` is controlled by its argument `extractfn`. This is a short function that is applied either (i) to each simulated raw dataset (caphist object) (`fit = FALSE`), or (ii) to each fitted model (`fit = TRUE`).

The default (builtin) `extractfn` (Appendix 1) behaves appropriately for either data type. It is mostly concerned with summarising raw counts when `fit = FALSE`. A dataframe with no rows is returned when a model fails to fit.

When `fit = FALSE`, the default output from each replicate is a vector of 4 summary statistics:

- `n` - number of different individuals
- `ndet` - total number of detections (‘captures’ and ‘recaptures’)
- `nmov` - total number of detections at a detector other than the one where an animal was last detected
- `dpa` - detectors per animal (average number of detectors at which each animal was recorded)

When `fit = TRUE`, the default output from each replicate is the result of applying `predict` to the fitted model, i.e. a dataframe of ‘real’ parameter estimates and their standard errors etc. (an empty dataframe is returned if model fitting fails). Nearly the same is achieved by setting `extractfn = predict` for the ‘beta’ coefficients set `extractfn = coef`. For a conditional likelihood fit it may be appropriate to set `extractfn = derived`. To focus on population size in the masked region, set `extractfn = region.N`.

The user may also choose to save the entire dataset (`fit = FALSE`) or the entire fitted model (`secr` object; `fit = TRUE`) for each replicate by setting `extractfn = identity`. For a large analysis there is a risk of exceeding memory limits in R, and saving everything is generally not a good idea. For most purposes it is sufficient to save a trimmed version of the fitted model `extractfn = trim` (note `secr` defines the function `trim`). However, the full model is needed for `derived` or `region.N` (see Extracting estimate tables from fitted models).

`run.scenarios()` sets the class¹ of its output to distinguish among fitted models (“fittedmodels”), estimate tables from `predict`, `coef` etc. (“`estimatetables`”), and numeric values ready for summarisation (“`selectd-statistics`”). Simulated data saved with `fit = FALSE`, `extractfn = identity` have class `c(“rawdata”, “secrdesign”, “list”)`. An attribute ‘`outputtype`’ is used to make finer distinctions among these types of output (“`secrfit`”, “`predicted`”, “`coef`”, “`capthist`”, or “`numeric`”). Output from `extractfn = derived` is treated as “`predicted`”.

When `fit = TRUE`, analyses are performed with `secr.fit`. Other analyses may be specified by setting `fit = FALSE` and providing the analysis function as the value for `extractfn`. The function should accept a ‘`capthist`’ object as input. For example, conventional closed-population estimates may be obtained with

```
closedNsim <- run.scenarios (nrepl = 10, scenarios = scen1, trapset = traps1,
  extractfn = closedN, estimator = c("null", "chao", "chaomod"))
```

```
## Completed scenario 1
```

```
## Completed scenario 2
```

```
## Completed in 0.007 minutes
```

This applies various *nonspatial* estimators to simulated *spatial* samples. Named arguments of `extractfn` may be included (here, ‘`estimator`’); these are used for all scenarios, unlike `fit.args` which may vary among scenarios. Summarisation of alternative analyses will usually require careful selection of ‘`parameter`’ and ‘`statistics`’ in `select.stats` (see Choosing the statistics to summarise).

An alternative is to write your own code along these lines:

```
sum1 <- function(out) {
  require(abind)
  ## collapse replicates to an array, omitting non-numeric column
  out <- do.call(abind, c(out, along = 3))[, -1, drop = FALSE]
  ## convert array from character to numeric
  mode(out) <- "numeric"
  ## take the average over replicates (meaningless for some fields)
  apply(out, 1:2, mean, na.rm = TRUE)
}
lapply(closedNsim$output, sum1)
```

More on masks

A habitat mask in `secr` is a raster representation of the region near the detectors in which the centres of detected animals may lie. This excludes both nearby non-habitat, and habitat that is so distant that it is implausible any animal centred there would reach a detector. It is often convenient to define a mask to include all cells whose centre is within a certain distance of a detector - the buffer radius.

Within `secrdesign`, a mask is used both when generating populations of animals with `sim.popn` and when fitting SECR models with `secr.fit`. The extent of the mask used to generate populations is important if you are concerned with population size (for example, if you set `extractfn = region.N`). Then the size of

¹the full class is actually `c(x, “secrdesign”“,”list“)` where `x` is as described.

the region determines the true value of the parameter of interest (N), and influences its sampling variance. The extent of the mask is less critical when density is the parameter of interest.

The default behaviour of `run.scenarios()` is to use a concave buffer of width `xsigma` \times `sigma` around the particular detector layout. The ‘coarseness’ of the mask is determined by `nx`; note that the default for `run.scenarios` (`nx` = 32) is coarser than the default for `secr::make.mask` (`nx` = 64). This makes for speed, and is fairly safe when the buffer width is well matched to the scale of movement (we know `sigma`, so the default buffer width *is* well-matched). The same mask is used both for generating populations and fitting models.

Users may specify their own masks in the ‘maskset’ list argument. If the number of masks in maskset is one or a number equal to the number of detector layouts, then a column ‘maskindex’ is added automatically to the scenarios dataframe (all 1, or equal to `trapsindex`, in the two cases). Otherwise, the user must have manually added a `maskindex` column to scenarios to clarify which mask should be used with which scenario.

Summarising simulation output

`run.scenarios` usually takes a long time to run, but having saved its output you can quickly extract and summarise the results in many different ways.

We saw in the previous section and Fig. 1 that the output from `run.scenarios` for each replicate may be a fitted model, a table of parameter estimates, or a numeric vector. Summarisation across replicates (the `summary` method) requires output in ‘selected statistics’ form, so each of the other forms must be processed first²

Look again at Fig. 1: you will see that the primary input to the `summary` function is in the form of selected statistics. A secondary route is to automatically extract statistics from estimates tables, as shown by the dashed line in Fig. 1 – we used this in A simple example. We now address how other forms of output from `run.scenarios` can be processed into ‘selected statistics’ form.

Extracting estimate tables from fitted models

The methods `predict`, `coef`, `derived` and `region.N` for the ‘fittedmodels’ class are provided to extract estimates of ‘real’ parameters from each fitted model. These are direct analogues of `predict`, `coef`, `derived` and `region.N` in **secr**. Here, they apply across all replicates of all scenarios and return an object of class `estimatetables`.

In each case, the result is a dataframe or list of dataframes for each replicate. Rows correspond to estimated parameters (or ‘R.N’ and ‘E.N’ for `region.N`) and columns to the respective estimates, standard errors, and confidence limits (with some variations).

The ... argument of the functions `predict`, `coef`, `derived` and `region.N` lets you pass arguments such as `alpha` to the corresponding `secr` function (e.g., `predict.secr` or `derived.secr`).

We can skip this step for the output from our simple example as it is already in ‘`estimatetables`’ form.

Choosing the statistics to summarise

Given tabular output from `predict()` or `derived()`, we must select replicate-specific numerical quantities for further summarisation.³ This is the role of `select.stats()`, which has arguments –

²Processing happens silently using default settings of `select.stats()` when `summary` is applied directly to ‘estimate tables’ output.

³If `run.scenarios()` has been used with `fit` = FALSE, then the output from each replicate is probably already in the form of selected statistics (the default raw data summaries ‘n’, ‘ndet’, ‘nmov’ and ‘dpa’) and `select.stats()` is not relevant. The same may also apply with a user-provided `extractfn` when `fit` = TRUE.

```
select.stats(object, parameter = "D", statistics)
```

The parameter of interest defaults to density ("D"); others such as "g0" or "sigma" may be substituted, so long as they appear in the input object. To check which parameters are available use

```
find.param(object)
```

The task of `select.stats()` is to reduce each replicate to a vector of numeric values - we can think of the result as a replicate \times values matrix for each scenario (Fig. 2). A later step (see Summary method) computes statistics ('fields') such as mean and SE for each column in the matrix.




Fig. 2. Operation of `select.stats` for one scenario. Each replicate contributes one row to a replicates \times statistics matrix.

Here we describe the replicate-specific statistics that form the numeric vector. These may be simply ‘estimate’, ‘SE.estimate’, ‘lcl’ and ‘ucl’ as output from `predict.secr`. Additionally, when `fit = TRUE`, we can include statistics derived from the estimates of a parameter (Table 1). To describe these we use ‘true’ to stand for the known value of a real parameter, and ‘estimate’ for the estimate from a particular replicate.

Table 1. Computed statistics available in `select.stats()`

Statistic	Short name	Value
Relative bias ¹	RB	(estimate – true) / true
Relative SE ²	RSE	SE.estimate / estimate
Absolute deviation	ERR	abs(estimate – true)
Coverage indicator	COV	(estimate > lcl) & (estimate < ucl)

1. Also called ‘normalized bias’
2. Also called ‘coefficient of variation’

We use ‘lcl’, ‘ucl’ to represent a confidence interval for ‘estimate’. Usually these are 95% intervals, but the level may be varied by setting the argument ‘alpha’ in `predict` (e.g., `alpha = 0.1` for a 90% interval). Intervals from `predict.secr` are symmetrical on the link scale, and hence asymmetrical on the natural scale. Note also the argument `loginterval` in `derived`; the default `loginterval = TRUE` gives an asymmetrical interval on the natural scale.

The coverage indicator COV is a binary value (0/1); this becomes interesting later when averaged over a large number of replicates to give a coverage proportion. The absolute deviation ERR also comes into its own later as the basis for RMSE. In a sense the same is true of replicate-specific RB: RB should be reported only as an average over a large number of replicates.

Returning to our simple example, we apply `select.stats()` to focus on the density parameter “D”.

```
stats1 <- select.stats(sims1, parameter = "D", statistics = c("estimate",
  "lcl", "ucl", "RB", "RSE", "COV"))
lapply(stats1$output, head, 4)
```

```
## $`1`
##   estimate      lcl      ucl      RB      RSE COV
## 1 5.151808 3.368614 7.878947 0.03036167 0.2193337 1
## 2 5.855274 4.016081 8.536738 0.17105476 0.1941624 1
## 3 4.482258 2.949922 6.810564 -0.10354842 0.2159012 1
## 4 4.883662 3.270895 7.291628 -0.02326768 0.2066668 1
##
## $`2`
##   estimate      lcl      ucl      RB      RSE COV
## 1 9.409474 7.045666 12.56633 -0.05905264 0.1484146 1
## 2 9.166823 6.787851 12.37957 -0.08331768 0.1542019 1
## 3 9.134215 6.781993 12.30227 -0.08657850 0.1528000 1
## 4 9.165342 6.812591 12.33062 -0.08346582 0.1522293 1
```

The two scenarios yield two replicates \times statistic matrices, from which we display the first 4 rows.

Disposing of rogue values

Simulation output may contain rogue values due to idiosyncracies of model fitting. For example, nonidentifiability due to inadequate data can result in spurious extreme estimates of the sampling variance. The median (chosen as a field value in `summary`) is recommended as a robust alternative to the mean when there are some

extreme estimates. Another way to deal with the problem is to set statistics to NA when a simulation fails. The function `validate` sets selected ‘target’ statistics to NA for replicates in which another test statistic is out-of-range or NA:

```
x <- validate(x, test, validrange = c(0, Inf), targets = test)
```

The permissible bounds are usually arbitrary, and the method should be used with care. The keyword “all” may be used for `targets` to indicate all columns.

`validate` accepts a `selectedstatistics` object (`x`) as input and returns a modified `selectedstatistics` object as output. See Learned trap response for an application.

Summary method

The `summary` method for ‘`selectedstatistics`’ objects reports both header information on the simulation scenarios and user-selected summaries of the pre-selected statistics.

```
summary(object, dec = 5, fields = c("n", "mean", "se"), alpha = 0.05,
        type = c("list", "dataframe", "array"), ...)
```

Here the summary statistics are called ‘fields’ to distinguish them from the ‘statistics’ in each column of the numeric replicate \times value matrix for each scenario (see Choosing the statistics to summarise). The task of the summary method is to compute the ‘field’ value for each ‘statistic’, summarising across replicates to give a ‘statistic’ \times ‘field’ matrix for each scenario. The choice of ‘fields’ is shown in Table 2.

Table 2. Statistic fields available in the `summary` method for `selectedstatistics` objects.

Field	Description
n	number of non-missing values
mean	mean
se	standard error
sd	sample standard deviation
min	minimum
max	maximum
lcl	lower $100(1 - \alpha)$ % confidence limit
ucl	upper $100(1 - \alpha)$ % confidence limit
rms	root mean square
median	median
qxxx	xxx/1000 quantile
qyyy	yyy/1000 quantile

The summary fields ‘lcl’ and ‘ucl’ are for a simple Wald interval $(\hat{\mu} + z_{\alpha/2}\widehat{SE}(\hat{\mu}), \hat{\mu} + z_{1-\alpha/2}\widehat{SE}(\hat{\mu}))$ where z_{α} is the 100α -percentile of a standard normal distribution (e.g., $z_{0.975} = 1.96$). [Do not confuse these with the confidence limit statistics of the same name that are symmetrical only on the link scale].

Quantiles are specified as ‘qxxx’ and ‘qyyy’ where xxx and yyy are integers between 1 and 999 corresponding to quantiles 0.001 to 0.999. For example, ‘q025’ refers to the 2.5% quantile.

Applying the ‘rms’ field to the absolute deviation of an estimate (ERR) provides the root-mean-square-error ‘RMSE’.

To recap – a summary value is reported for each combination of a selected statistic, computed for each replicate, and a ‘field’ that summarises the statistic across replicates, potentially resulting in a table with this structure:

	Fields											
Statistics	n	mean	se	sd	min	max	lcl	ucl	rms	median	q025	q975
estimate	*	*	*	*	*	*	*	*		*	*	*
SE.estimate	*	*	*	*	*	*	*	*		*	*	*
lcl	*	*	*	*	*	*				*	*	*
ucl	*	*	*	*	*	*				*	*	*
RB	*	*	*	*	*	*				*	*	*
RSE	*	*	*	*	*	*	*	*		*	*	*
ERR	*	*	*	*	*	*	*	*	*	*	*	*
COV	*	*	*	*	*	*						

Cells are left blank for combinations that are unlikely to be meaningful. ‘rms’ is useful with ERR (i.e. RMSE), but not when applied to other statistics. ‘n’, ‘mean’ and ‘se’ summarise the COV indicator, but other potential summaries are (almost) meaningless.

Apply this to the selected statistics from our simple example:

```
summary(stats1, c('n', 'mean', 'se', 'median'))
```

```
## run.scenarios(nrepl = 50, scenarios = scen1, trapset = traps1,
##      fit = TRUE, fit.args = list(detectfn = "HHN"), seed = 345)
##
## Replicates      50
## Started         17:18:49 01 Dec 2017
## Run time        3.171  minutes
## Output class    selectedstatistics
##
## $constant
##      value
## trapsindex      1
## noccasions      3
## nrepeats        1
## g0              0.2
## sigma           25
## detectfn        0
## recapfactor     1
## popindex        1
## detindex        1
## fitindex        1
## maskindex       1
##
## $varying
##  scenario  D
##         1  5
##         2 10
##
## $detectors
##  trapsindex trapsname
##         1    traps1
##
## $fit.args
##  fitindex detectfn
##         1      HHN
##
## OUTPUT
##
```

```
## $1
## 1
##      n      mean      se  median
## estimate 50 5.02808 0.15602 5.04639
## lcl      50 3.35008 0.12476 3.29861
## ucl      50 7.56696 0.18881 7.68861
## RB       50 0.00562 0.03120 0.00928
## RSE      50 0.21583 0.00426 0.21136
## COV      50 0.98000 0.02000 1.00000
##
## $2
## 2
##      n      mean      se  median
## estimate 50 9.86995 0.20303 9.91979
## lcl      50 7.38442 0.17085 7.37450
## ucl      50 13.19702 0.23887 13.34368
## RB       50 -0.01301 0.02030 -0.00802
## RSE      50 0.15023 0.00142 0.14992
## COV      50 0.96000 0.02799 1.00000
```

Plot method

Use the plot method to visualize the distributions of ‘selectedstatistics’ that you have simulated. You may plot either (i) histograms of the selected statistics (`type = "hist"`) or (ii) the estimate and confidence interval for each replicate (`type = "CI"`). One histogram is plotted for each combination of scenario and statistic – you may want to select a subset of scenarios and statistics, and use the graphics options `mfc` or `mfrow` to control the layout. For `type = "CI"` the statistics must include ‘estimate’, ‘lcl’ and ‘ucl’ (or ‘beta’, ‘lcl’ and ‘ucl’ if `outputtype = "coef"`).

```
par(mfrow = c(2,2))
plot(stats1, type = "hist", statistic = "estimate")
plot(stats1, type = "CI")
```




Fig. 3. Plot method applied to a 2-scenario ‘selectedstatistics’ object with `type = "hist"` (top) and `type = "CI"` (bottom)

Additional topics

Parallel processing

Setting `ncores > 1` causes `run.scenarios()` to run separate scenarios on separate cores (given the default `byscenario = TRUE`). This uses the R package **parallel**. Technically, it relies on Rscript, and communication between the master and worker processes is via sockets. As stated in the R **parallel** documentation “Users of Windows and Mac OS X may expect pop-up dialog boxes from the firewall asking if an R process should accept incoming connections”. It appears to be safe to accept these.

Use `parallel::detectCores()` to get an idea of how many cores are available on your machine; this may (in Windows) include virtual cores over and above the number of physical cores. If you use the maximum available cores for `run.scenarios()` then expect any other processes on the machine to slow down!

Running one scenario per core is suboptimal if scenarios differ widely in how long they take to run: the system waits for the slowest. Setting `byscenario = FALSE` provides a way around this: replicates within a scenario are divided among cores, instead of all replicates going to one core.

Random number generation for multiple cores uses the “L’Ecuyer-CMRG” random number generator as described in `?RNG`.

Shortcut evaluation of precision

The asymptotic variance (and hence RSE) of a maximum likelihood estimate is typically obtained from the curvature of the likelihood computed numerically at the fitted value of the parameter(s) (i.e., at the MLE). Fitting SECR models is slow. An alternative estimate of the RSE that is sufficient for most purposes may be got from the curvature of the likelihood computed at the known ‘true’ value(s) of the parameter(s). This is much faster as it does not require the model to be fitted.

`secr.fit` may be ‘tricked’ into providing this variance estimate by setting `method = "none"` and providing the true values as the `start` vector. `run.scenarios()` makes this easy by assuming that if you specify `method = "none"` you wish to use `start = "true"`. However, this works only when there is a 1:1 relationship between ‘beta’ and ‘real’ parameters; it does not work when ‘recapfactor’ is specified.

```
sims2 <- run.scenarios(nrepl = 50, trapset = traps1, scenarios = scen1,
  fit = TRUE, fit.args = list(method = "none"))
```

```
## Completed scenario 1
```

```
## Completed scenario 2
```

```
## Completed in 0.571 minutes
```

```
summary(sims2)
```

```
## run.scenarios(nrepl = 50, scenarios = scen1, trapset = traps1,
##   fit = TRUE, fit.args = list(method = "none"))
```

```
##
```

```
## Replicates      50
```

```
## Started         17:22:00 01 Dec 2017
```

```
## Run time        0.571 minutes
```

```
## Output class    selectedstatistics
```

```
##
```

```
## $constant
```

```
##           value
```

```
## trapsindex      1
```

```
## noccasions      3
```

```
## nrepeats        1
```

```
## g0              0.2
```

```
## sigma           25
```

```
## detectfn        0
```

```
## recapfactor     1
```

```
## popindex        1
```

```
## detindex        1
```

```
## fitindex        1
```

```
## maskindex       1
```

```
##
```

```
## $varying
```

```
##   scenario D
```

```
##       1  5
```

```
##       2 10
```

```
##
```

```
## $detectors
```

```
## trapsindex trapsname
```

```
##       1      traps1
```

```
##
```

```
## $fit.args
```

```
## fitindex method
```



```
##          1   none
##
## OUTPUT
##
## $1
## 1
##           n      mean      se
## estimate  50  5.00000  0.00000
## SE.estimate 50  1.06702  0.00572
## lc1        50  3.30672  0.00705
## uc1        50  7.56210  0.01658
## RB         0      NA      NA
## RSE        50  0.21340  0.00114
## COV        0      NA      NA
##
## $2
## 2
##           n      mean      se
## estimate  50 10.00000  0.00000
## SE.estimate 50  1.48331  0.00397
## lc1        50  7.48916  0.00573
## uc1        50 13.35301  0.01022
## RB         0      NA      NA
## RSE        50  0.14833  0.00040
## COV        0      NA      NA
```

Each estimate of RSE is essentially the same as before (see `summary(stats1)` in Summary method), but the run time is reduced by nearly 80%. Note the true value of density appears as a constant ‘estimate’ in the summary. Care is needed with this method as its performance in extreme cases has not been investigated fully.

Non-uniform populations

The simulated population by default has a uniform (homogeneous) Poisson distribution. To generate and sample from a spatially inhomogeneous population we use the ‘IHP’ option for argument `model2D` in `seccr::sim.popn`. This involves three steps:

1. Create a habitat mask object with the desired extent.
2. Add to the mask a covariates dataframe with one or more columns defining pixel-specific densities.
3. In `run.scenarios()` specify a list of `pop.args` including `model2D = "IHP"` and `D = "XX"` where `XX` is the name of the particular mask covariate you wish to use for density, and name your mask in the ‘maskset’ argument.

A full demonstration is given in Appendix 2 (Non-uniform possums).

To visualize simulated populations you should set `savepopn = TRUE` in `det.args` and later extract the `popn` attribute from the `capthist` object (for example, with a custom `extractfn`).

To compare several inhomogeneous distributions, specify several `pop.args` lists and use the `popindex` argument in `make.scenarios()`. The distribution may be varied simply by using the `sim.popn()` argument `D` to select different covariates of one mask.

The columns ‘nrepeats’ and ‘D’ in the `scenarios` argument of `run.scenarios` are ignored when `model2D = "IHP"`. ‘D’ is replaced by the average density over the mask, which is used as the ‘true’ value of density in computing RB, RSE etc. in summaries. For stratified analyses you will have to define your own `extractfn`.

Linear habitat

secdesign may be used to simulate sampling of populations in linear habitats as implemented in R package **seclinear**. The procedure is similar to that for non-uniform (inhomogeneous Poisson) populations as described in the previous section: one or more masks must be provided, but in this case they will be of type ‘linearmask’.

The steps are:

1. Create linear habitat mask objects with the desired extent.
2. Create detector layouts and a scenario dataframe as usual.
3. Add a ‘maskindex’ column to the scenarios dataframe identifying which mask is to be used in each scenario (may be omitted for a single mask).
4. In `run.scenarios()` specify your mask(s) in the `maskset` argument.

Density may be specified in the scenario dataframe as a constant number of animals per km, and in this case the ‘nrepeats’ column is respected.

Density also may be modelled as inhomogeneous, i.e. varying along the length of the linear mask. The mechanism for this is like that for two dimensions: use a list of `pop.args` including `model2D = "linear"` and `D = "XX"` where `XX` is the name of the particular mask covariate you wish to use for density. In this case, the columns ‘nrepeats’ and ‘D’ in the scenarios dataframe are ignored, as for the ‘IHP’ option.

With a linear mask, `run.scenarios` defaults to `seclinear::networkdistance` for the distance function (`secl.fit` argument `details$userdist`).

Splitting data generation and model fitting

Each new detector layout or new model specification (in a `fit.args` list) defines a new scenario. The default procedure is to generate new data (both animal locations and simulated detection histories) for each scenario. To compare different models applied to the same dataset, save raw data from an initial call to `run.scenarios()` with `fit = FALSE`, `extractfn = identity`, and separately fit a list of models with `fit.models`. You can also peek at the raw data with the `summary` method.

```
scen3 <- make.scenarios(D = c(5,10), sigma = 25, g0 = 0.2)
traps3 <- make.grid()
raw3 <- run.scenarios(nrepl = 50, trapset = traps3, scenarios =
  scen3, fit = FALSE, extractfn = identity)
```

```
## Completed scenario 1
## Completed scenario 2
## Completed in 0.008 minutes
```

```
summary(raw3)
```

```
## Completed scenario 1
## Completed scenario 2
## Completed in 0.005 minutes
## fit.models(rawdata = object)
##
## Replicates      50
## Started         17:22:35 01 Dec 2017
## Run time        0.005 minutes
## Output class    selectedstatistics
```

```

##
## $constant
##           value
## trapsindex      1
## noccasions      3
## nrepeats        1
## g0              0.2
## sigma           25
## detectfn        0
## recapfactor     1
## popindex        1
## detindex        1
## fitindex        1
## maskindex       1
##
## $varying
## scenario D
##           1 5
##           2 10
##
## $detectors
## trapsindex trapsname
##           1   traps1
##
## OUTPUT
##
## $1
## 1
##      n      mean      se
## n    50 15.36000 0.60391
## ndet 50 28.80000 1.16374
## nmov 50 12.30000 0.63391
## dpa  50  1.78397 0.02972
## rse  50  0.38835 0.00838
##
## $2
## 2
##      n      mean      se
## n    50 27.80000 0.68512
## ndet 50 51.84000 1.43665
## nmov 50 21.74000 0.78601
## dpa  50  1.75619 0.02021
## rse  50  0.28414 0.00430
## fit and summarise models
sims3 <- fit.models(raw3, fit.args = list(list(model = g0~1),
  list(model = g0~T)), fit = TRUE, ncores = 4, byscenario = FALSE)

## Completed scenario 1.1
## Completed scenario 1.2
## Completed scenario 2.1
## Completed scenario 2.2
## Completed in 1.737 minutes

```

```
summary(sims3)
```

```
## fit.models(rawdata = raw3, fit = TRUE, fit.args = list(list(model = g0 ~
##      1), list(model = g0 ~ T)), ncores = 4, byscenario = FALSE)
##
## Replicates      50
## Started         17:22:35 01 Dec 2017
## Run time        1.737 minutes
## Output class    selectedstatistics
##
## $constant
##           value
## trapsindex     1
## nooccasions     3
## nrepeats        1
## g0              0.2
## sigma           25
## detectfn        0
## recapfactor     1
## popindex        1
## detindex        1
## maskindex       1
##
## $varying
##  scenario D fitindex
##        1.1 5         1
##        1.2 5         2
##        2.1 10        1
##        2.2 10        2
##
## $detectors
## trapsindex trapsname
##          1   traps1
##
## $fit.args
## fitindex model
##          1 ~ g0 1
##          2 ~ g0 T
##
## OUTPUT
##
## $1.1
## 1.1
##           n      mean      se
## estimate  50  5.46452 0.29218
## SE.estimate 50  1.86874 0.05836
## lcl        50  2.87787 0.19784
## ucl        50 10.55931 0.40310
## RB         50  0.09290 0.05844
## RSE        50  0.36939 0.01385
## COV        50  0.90000 0.04286
##
## $1.2
## 1.2
```

```
##           n      mean      se
## estimate  50  5.34777 0.29288
## SE.estimate 50  1.83693 0.06191
## lcl       50  2.80467 0.19622
## ucl       50 10.34912 0.41909
## RB        50  0.06955 0.05858
## RSE       50  0.36773 0.01074
## COV       50  0.88000 0.04642
##
## $2.1
## 2.1
##           n      mean      se
## estimate  50  9.58835 0.32383
## SE.estimate 50  2.43988 0.05416
## lcl       50  5.88488 0.24301
## ucl       50 15.69643 0.42323
## RB        50 -0.04117 0.03238
## RSE       50  0.26214 0.00586
## COV       50  0.96000 0.02799
##
## $2.2
## 2.2
##           n      mean      se
## estimate  50  9.52179 0.32507
## SE.estimate 50  2.43182 0.05463
## lcl       50  5.83418 0.24359
## ucl       50 15.61520 0.42566
## RB        50 -0.04782 0.03251
## RSE       50  0.26320 0.00589
## COV       50  0.96000 0.02799
```

Here, `scen3` describes two scenarios, and in the call to `fit.models` each of these is split into two new scenarios, one for each component of `fit.args`.

The arguments ‘`scen`’ and ‘`repl`’ of `fit.models` let you select particular scenarios and replicates for fitting (`secrdesign` \geq 2.3.0).

It is not possible within `secrdesign` precisely to evaluate the application to the same animal distribution (population) of differing detector layouts or specifications for the fitted model (cf Fewster and Buckland 2004). Comparisons inevitably include variance from the varying number and placement of animals, and the sampling process; this variance may be reduced by fixing the number of individuals (`pop.args = list(Ndist = "fixed")`).

Populations with sub-classes or multiple sessions

Simulation of structured populations is introduced in `secrdesign` 2.2.0 and is still experimental.

The ‘`groups`’ argument of `make.scenarios` replicates rows so that within a scenario there is one row for each group. Group-specific parameter values are inserted by the user.

Rows sharing the same scenario number are recognised by `run.scenarios` as subclasses (groups). Each subclass is generated as a separate `capthist` object. The argument `multisession` determines whether the `capthist` objects corresponding to subclasses are pooled for analysis (using `secr::rbind.capthist`) or treated as multiple distinct sessions (using `secr::MS.capthist`).

The original sub-class of each individual is recorded as an individual covariate named “group”. This is a

factor. It may be ignored in the fitted model, or used in such `secr.fit` arguments as ‘groups’ and ‘hcov’, or included in models directly as an individual covariate when `CL = TRUE`. (If the output from `predict.secr` is not a single dataframe then you will have to write a custom `extractfn`).

An example is given in Appendix 2 (Grouped populations).

Limitations, tips and troubleshooting

`secrdesign` has some limitations (Surprise!).

1. A progress message is output only on the completion of each scenario, which can be annoying, and when using multiple cores even this message is lost. It is strongly recommended that you start by generating summaries of raw data only (`run.scenarios()` with `fit = FALSE`), and confirm that your scenarios are realistic by reviewing the simulated number of detected individuals, total number of detections, etc. If these are inadequate or unrealistically large then there’s no point going on. Then, try fitting with just a few replicates on one core to be sure you have specified the model you intended and to assess the likely run time. Only then submit a run with a large number of replicates on multiple cores.
2. Only 2-parameter detection functions are allowed for data generation. This excludes the hazard-rate function, the cumulative gamma, and some others.
3. The default `extractfn` does not handle models that produce more than one estimates table per replicate (e.g., finite mixture models). A custom `extractfn` is needed; it should either produce a numeric vector of ‘selected statistics’ or mimic single-dataframe output from `predict()`.
4. The function `secr::sim.capthist` that generates detection histories for `secrdesign` has limited capacity for simulating temporal, behavioural or other heterogeneity in detection probability. Heterogeneity may be simulated as discrete subclasses (see preceding section). Only a simple permanent learned response is allowed in `run.scenarios` (‘recapfactor’).
5. As noted before, the same mask is used for generating populations and fitting models. It would be possible to replace the maskset component of a ‘rawdata’ object before running `fit.models`, but this is not recommended.
6. It is easy to forget the random number seed. Consider replacing the default value.
7. The method for fitting a fixed-N model (`distribution = binomial`) is somewhat fragile: it can fail when given a start value for D that is less than the minimum density observed (i.e. the number of distinct individuals divided by the mask area). This can easily happen when a population is simulated with `pop.args = list(Ndist = "poisson")` (the default) and sampled with high detection probability, but `secr.fit` is called with (`distribution = "binomial"`). The solution is to use `pop.args = list(Ndist = "fixed")`.
8. If your summaries do not include enough significant digits, increase the ‘dec’ argument of `summary.selectedstatistics!`

References

Borchers, D. L. and Efford, M. G. (2008) Spatially explicit maximum likelihood methods for capture–recapture studies. *Biometrics* **64**, 377–385.

Cooch, E. and White, G. (eds) (2014) *Program MARK: A Gentle Introduction*. 13th edition. Available online at <http://www.phidot.org/software/mark/docs/book/>.

Efford, M. G. (2012) DENSITY 5.0: software for spatially explicit capture–recapture}. Department of Mathematics and Statistics, University of Otago, Dunedin, New Zealand <http://www.otago.ac.nz/density>.

- Efford, M. G., Borchers D. L. and Byrom, A. E. (2009) Density estimation by spatially explicit capture–recapture: likelihood-based methods. In: D. L. Thomson, E. G. Cooch, M. J. Conroy (eds) *Modeling Demographic Processes in Marked Populations*. Springer. Pp 255–269.
- Efford, M. G., Dawson, D. K. and Borchers, D. L. (2009) Population density estimated from locations of individuals on a passive detector array. *Ecology* **90**, 2676–2682.
- Efford, M. G. and Fewster, R. M. (2013) Estimating population size by spatially explicit capture–recapture. *Oikos* **122**, 918–928.
- Fewster, R. M. and Buckland, S. T. (2004) Assessment of distance sampling estimators. In: S. T. Buckland, D. R. Anderson, K. P. Burnham, J. L. Laake, D. L. Borchers and L. Thomas (eds) *Advanced distance sampling*. Oxford University Press, Oxford, U. K. Pp. 281–306.
- Williams, B. K., Nichols, J. D. and Conroy, M. J. (2002) *Analysis and management of animal populations*. Academic Press, San Diego

Appendix 1. Default extractfn for run.scenarios.

```
defaultextractfn <- function(x) {
  if (inherits(x, 'try-error')) {
    ## null output: dataframe of 0 rows and 0 columns
    data.frame()
  }
  else if (inherits(x, 'capthist')) {
    ## summarised raw data
    counts <- function(CH) {
      ## for single-session CH
      if (nrow(CH)==0) { ## 2015-01-24
        if (sighting(traps(CH)))
          c(n = 0, ndet = 0, nmov = 0, dpa = 0,
            unmarked=0, nonID = 0, nzero = 0)
        else
          c(n=0, ndet=0, nmov=0, dpa = NA)
      }
      else {
        n <- nrow(CH)
        ndet <- sum(abs(CH)>0)
        r <- ndet - n
        nmoves <- sum(unlist(sapply(moves(CH), function(y) y>0)))
        ## detectors per animal
        dpa <- if (length(dim(CH)) == 2)
          mean(apply(abs(CH), 1, function(y) length(unique(y[y>0]))))
        else
          mean(apply(apply(abs(CH), c(1,3), sum)>0, 1, sum))
        if (sighting(traps(CH))) {
          unmarked <- if (is.null(Tu <- Tu(CH))) NA else sum(Tu)
          nonID <- if (is.null(Tm <- Tm(CH))) NA else sum(Tm)
          nzero <- sum(apply(abs(CH), 1, sum) == 0)
          c(n = n, ndet = ndet, nmov = nmoves, dpa = dpa,
            unmarked=unmarked, nonID = nonID, nzero = nzero)
        }
        else
          c(n=n, ndet=ndet, nmov=nmoves, dpa = dpa, rse = sqrt(1/n + 1/r))
      }
    }
    if (ms(x))
      unlist(lapply(x, counts))
    else {
      gp <- covariates(x)$group
      if (is.null(gp))
        counts(x)
      else
        unlist(lapply(split(x, gp, dropnulloc=TRUE), counts))
    }
  }
  else if (inherits(x, 'segr') & (!is.null(x$fit))) {
    ## fitted model:
    ## default predictions of 'real' parameters
    out <- predict(x)
```



```

    if (is.data.frame(out))
      out
    else {
      warning ("summarising only first session, group or mixture class")
      out[[1]]
    }
  }
else
  ## null output: dataframe of 0 rows and 0 columns
  data.frame()
}

```

Appendix 2. Examples

Here we give some annotated examples of simulation code and selected output. Running this code with reduced `nrepl`, and viewing the output, will give you an idea of how `secrdesign` works.

Multiple grids, varying number of occasions

This is the example from the main text, slightly extended

```

traps4 <- list(grid6x6 = make.grid(6,6),
              grid8x9 = make.grid(8,9),
              grid12x12 = make.grid(12,12))
scen4 <- make.scenarios (trapsindex = 1:3, noccasions = c(8,4,2), D = 5,
                       g0 = 0.2, sigma = c(20,30), crosstraps = FALSE)

sims4 <- run.scenarios(nrepl = 500, trapset = traps4, scenarios =
                     scen4, fit = FALSE, ncores = 3)

```

```
## Completed in 0.513 minutes
```

```
class(sims4)      ## just peeking
```

```
## [1] "selectedstatistics" "secrdesign"      "list"
```

```
find.stats(sims4)  ## just peeking
```

```
## [1] "n"      "ndet" "nmov" "dpa"  "rse"
```

```
summary(sims4)
```

```
## run.scenarios(nrepl = 500, scenarios = scen4, trapset = traps4,
##               fit = FALSE, ncores = 3)
##
```

```
## Replicates      500
## Started         17:24:20 01 Dec 2017
## Run time        0.513  minutes
## Output class    selectedstatistics
##
## $constant
##           value
## nrepeats      1
## D             5

```

```

## g0          0.2
## detectfn    0
## recapfactor 1
## popindex    1
## detindex    1
## fitindex    1
##
## $varying
##  scenario trapsindex noccasions sigma maskindex
##        1         1         8     20         1
##        2         2         4     20         2
##        3         3         2     20         3
##        4         1         8     30         4
##        5         2         4     30         5
##        6         3         2     30         6
##
## $detectors
##  trapsindex trapsname
##          1  grid6x6
##          2  grid8x9
##          3 grid12x12
##
## OUTPUT
##
## $1
##  1
##      n      mean      se
## n    500 14.57400 0.16815
## ndet 500 51.45400 0.71026
## nmov 500 31.36600 0.50628
## dpa  500  2.78102 0.01919
## rse  500  0.32077 0.00227
##
## $2
##  2
##      n      mean      se
## n    500 21.32800 0.19896
## ndet 500 48.25000 0.50361
## nmov 500 23.69600 0.30534
## dpa  500  2.04600 0.00939
## rse  500  0.29717 0.00165
##
## $3
##  3
##      n      mean      se
## n    500 32.79600 0.25612
## ndet 500 47.69400 0.39459
## nmov 500 13.31400 0.16687
## dpa  500  1.40546 0.00405
## rse  500  0.32102 0.00195
##
## $4
##  4
##      n      mean      se

```

```
## n      500 23.16000 0.21425
## ndet  500 93.15600 0.99874
## nmov  500 63.43600 0.76735
## dpa   500  3.37465 0.01877
## rse   500  0.24506 0.00136
##
## $5
##      n      mean      se
## n      500 31.34400 0.24730
## ndet  500 81.16000 0.70469
## nmov  500 46.24600 0.47272
## dpa   500  2.40957 0.00952
## rse   500  0.23152 0.00099
##
## $6
##      n      mean      se
## n      500 45.45600 0.30255
## ndet  500 73.76600 0.49468
## nmov  500 26.58400 0.21597
## dpa   500  1.58586 0.00312
## rse   500  0.24199 0.00086
```

```
par(mfrow = c(4,3), cex=0.8, mgp=c(2.2,0.6,0))
plot(sims4, statistic = "n", breaks = seq(0,80,5))      ## animals
plot(sims4, statistic = "nmov", breaks = seq(0,140,5)) ## movements
```




Fig. 4. Numbers of individuals (n) and movements (nmov) from six scenarios differing in trap number, number of sampling occasions and scale of movement.

Learned trap response

Here we assess the bias in \hat{D} caused by ignoring a learned trap response.

```
## set up and run simulations
traps5 <- list(grid6x6 = make.grid(6,6),
               grid10x10 = make.grid(10,10))
scen5 <- make.scenarios (trapsindex = 1:2, noccasions = 5, D = 5,
                        g0 = 0.2, sigma = 25, recapfactor = c(0.5, 1, 2), fitindex = 1:2)
sims5 <- run.scenarios(nrepl = 500, trapset = traps5, scenarios =
                      scen5, fit = TRUE, fit.args = list(list(model = g0 ~ 1),
                  list(model = g0 ~ b)), ncores = 6)
```

```
## Completed in 91.061 minutes
```

```
## select statistics and throw out any replicates with SE > 100, if any
stats5 <- select.stats(sims5)
stats5 <- validate(stats5, "SE.estimate", c(0,100), "all")
```

```

## Dropping 0 value(s) for scenario 1
## Dropping 0 value(s) for scenario 2
## Dropping 0 value(s) for scenario 3
## Dropping 0 value(s) for scenario 4
## Dropping 0 value(s) for scenario 5
## Dropping 0 value(s) for scenario 6
## Dropping 0 value(s) for scenario 7
## Dropping 0 value(s) for scenario 8
## Dropping 0 value(s) for scenario 9
## Dropping 0 value(s) for scenario 10
## Dropping 0 value(s) for scenario 11
## Dropping 0 value(s) for scenario 12

sum5 <- summary(stats5, fields = c("n","mean","se","lcl","ucl", "median"))

## plot
plot(c(0.5,6.5), c(-0.2,0.4), type = "n", xlab = "Scenario", ylab = "RB(D-hat)")
for (i in 1:12) {
  xv <- if (i<=6) i else (i-6)+0.05
  segments(xv, sum5$OUTPUT[[i]]["RB","lcl"], xv, sum5$OUTPUT[[i]]["RB","ucl"])
  ptcol <- if (i<=6) "white" else "black"
  points(xv, sum5$OUTPUT[[i]]["RB","mean"], pch = 21, bg = ptcol)
}
abline(h = 0, col="red")
text(c(1.5,3.5,5.5), rep(0.38,3), paste("recapfactor", c(0.5,1,2), sep = " = "))

```




Fig. 5 Relative bias of SECR density estimate from null model (filled circles) and $g_0 \sim b$ model (open circles) when data were generated with negative, zero, or positive learned response.

```
## look at extended output
sum5

## run.scenarios(nrepl = 500, scenarios = scen5, trapset = traps5,
##   fit = TRUE, fit.args = list(list(model = g0 ~ 1), list(model = g0 ~
##     b)), ncores = 6)
##
## Replicates      500
## Started        17:33:02 02 Dec 2017
## Run time       91.061 minutes
## Output class   selectedstatistics
##
## $constant
##           value
## noccasions     5
## nrepeats       1
## D              5
## g0             0.2
## sigma         25
## detectfn       0
## popindex       1
## detindex       1
##
## $varying
## scenario trapsindex recapfactor fitindex maskindex
```

```

##      1      1      0.5      1      1
##      2      2      0.5      1      2
##      3      1      1.0      1      1
##      4      2      1.0      1      2
##      5      1      2.0      1      1
##      6      2      2.0      1      2
##      7      1      0.5      2      1
##      8      2      0.5      2      2
##      9      1      1.0      2      1
##     10      2      1.0      2      2
##     11      1      2.0      2      1
##     12      2      2.0      2      2
##
## $detectors
##  trapsindex trapsname
##      1  grid6x6
##      2  grid10x10
##
## $fit.args
##  fitindex  model
##      1 ~ g0 1
##      2 ~ g0 b
##
## OUTPUT
##
## $1
##  1
##
##      n      mean      se      lcl      ucl      median
## estimate    500  6.32217 0.08920  6.14734  6.49699  6.13434
## SE.estimate    500  1.96970 0.02066  1.92921  2.01019  1.91197
## lcl          500  3.50322 0.06041  3.38483  3.62162  3.37427
## ucl          500 11.52957 0.13354 11.26785 11.79130 11.16455
## RB           500  0.26443 0.01784  0.22947  0.29940  0.22687
## RSE          500  0.32530 0.00314  0.31914  0.33146  0.31211
## COV          500  0.87000 0.01506  0.84049  0.89951  1.00000
##
## $2
##  2
##
##      n      mean      se      lcl      ucl      median
## estimate    500  5.60377 0.04398  5.51758  5.68996  5.59366
## SE.estimate    500  1.01244 0.00455  1.00352  1.02136  1.01381
## lcl          500  3.94601 0.03588  3.87569  4.01633  3.93719
## ucl          500  7.96549 0.05269  7.86221  8.06877  7.95375
## RB           500  0.12075 0.00880  0.10352  0.13799  0.11873
## RSE          500  0.18341 0.00076  0.18192  0.18490  0.18088
## COV          500  0.88400 0.01434  0.85590  0.91210  1.00000
##
## $3
##  3
##
##      n      mean      se      lcl      ucl      median
## estimate    500  5.03246 0.06759  4.89999  5.16492  4.98136
## SE.estimate    500  1.49518 0.01317  1.46937  1.52099  1.48622
## lcl          500  2.85808 0.04706  2.76585  2.95031  2.80786
## ucl          500  8.92463 0.09436  8.73970  9.10956  8.84277

```

```

## RB          500 0.00649 0.01352 -0.02000 0.03298 -0.00373
## RSE          500 0.31024 0.00242  0.30549 0.31499  0.30036
## COV          500 0.94200 0.01046  0.92149 0.96251  1.00000
##
## $4
## 4
##           n      mean      se      lcl      ucl      median
## estimate   500  4.99059 0.03967  4.91284 5.06835  4.90610
## SE.estimate 500  0.88241 0.00374  0.87508 0.88974  0.87671
## lcl        500  3.54017 0.03272  3.47604 3.60431  3.46570
## ucl        500  7.04158 0.04690  6.94966 7.13349  6.92608
## RB         500 -0.00188 0.00793 -0.01743 0.01367 -0.01878
## RSE        500  0.17959 0.00073  0.17815 0.18102  0.17888
## COV        500  0.94000 0.01063  0.91916 0.96084  1.00000
##
## $5
## 5
##           n      mean      se      lcl      ucl      median
## estimate   500  4.38165 0.06039  4.26330 4.50001  4.29384
## SE.estimate 500  1.28323 0.01036  1.26293 1.30353  1.28837
## lcl        500  2.50823 0.04294  2.42408 2.59238  2.43474
## ucl        500  7.71061 0.08070  7.55245 7.86877  7.68428
## RB         500 -0.12367 0.01208 -0.14734 -0.10000 -0.14123
## RSE        500  0.30713 0.00244  0.30235 0.31190  0.29786
## COV        500  0.93600 0.01096  0.91453 0.95747  1.00000
##
## $6
## 6
##           n      mean      se      lcl      ucl      median
## estimate   500  4.64075 0.03776  4.56674 4.71476  4.64673
## SE.estimate 500  0.81774 0.00357  0.81075 0.82473  0.81724
## lcl        500  3.29584 0.03112  3.23483 3.35684  3.29534
## ucl        500  6.54036 0.04470  6.45276 6.62796  6.55043
## RB         500 -0.07185 0.00755 -0.08665 -0.05705 -0.07065
## RSE        500  0.17904 0.00073  0.17761 0.18047  0.17696
## COV        500  0.93400 0.01111  0.91222 0.95578  1.00000
##
## $7
## 7
##           n      mean      se      lcl      ucl      median
## estimate   500  5.08763 0.07369  4.94319 5.23207  4.98121
## SE.estimate 500  1.77119 0.02686  1.71854 1.82383  1.69433
## lcl        500  2.65465 0.04730  2.56195 2.74736  2.56097
## ucl        500  9.95563 0.14511  9.67122 10.24003  9.65926
## RB         500  0.01753 0.01474 -0.01136 0.04641 -0.00376
## RSE        500  0.36149 0.00388  0.35389 0.36910  0.34136
## COV        500  0.95600 0.00918  0.93800 0.97400  1.00000
##
## $8
## 8
##           n      mean      se      lcl      ucl      median
## estimate   500  4.96048 0.04070  4.88072 5.04024  4.92782
## SE.estimate 500  0.92198 0.00457  0.91302 0.93094  0.92029
## lcl        500  3.45869 0.03282  3.39436 3.52302  3.41335

```



```

## ucl      500  7.12171 0.04953  7.02462 7.21879  7.09260
## RB      500 -0.00790 0.00814 -0.02386 0.00805 -0.01444
## RSE     500  0.18874 0.00079  0.18720 0.19028  0.18733
## COV     500  0.95200 0.00957  0.93324 0.97076  1.00000
##
## $9
## 9
##          n      mean      se      lcl      ucl      median
## estimate  500  4.99471 0.07265  4.85232 5.13710  4.79112
## SE.estimate 500  1.62794 0.02174  1.58534 1.67054  1.55636
## lcl       500  2.70060 0.04766  2.60717 2.79402  2.54435
## ucl       500  9.35869 0.12433  9.11502 9.60237  8.97275
## RB        500 -0.00106 0.01453 -0.02954 0.02742 -0.04178
## RSE       500  0.33742 0.00291  0.33172 0.34311  0.32816
## COV       500  0.94800 0.00994  0.92852 0.96748  1.00000
##
## $10
## 10
##          n      mean      se      lcl      ucl      median
## estimate  500  5.01399 0.03668  4.94210 5.08587  4.97408
## SE.estimate 500  0.90888 0.00389  0.90126 0.91649  0.90842
## lcl       500  3.52647 0.02986  3.46794 3.58500  3.47750
## ucl       500  7.13497 0.04410  7.04854 7.22140  7.10889
## RB        500  0.00280 0.00734 -0.01158 0.01717 -0.00518
## RSE       500  0.18363 0.00073  0.18221 0.18506  0.18231
## COV       500  0.97600 0.00685  0.96257 0.98943  1.00000
##
## $11
## 11
##          n      mean      se      lcl      ucl      median
## estimate  500  5.04224 0.06524  4.91438 5.17011  4.89449
## SE.estimate 500  1.65677 0.05525  1.54849 1.76506  1.53358
## lcl       500  2.76299 0.04447  2.67584 2.85015  2.66744
## ucl       500  9.69966 0.36094  8.99224 10.40709  8.94337
## RB        500  0.00845 0.01305 -0.01712 0.03402 -0.02110
## RSE       500  0.33531 0.00762  0.32038 0.35024  0.31145
## COV       500  0.97000 0.00764  0.95503 0.98497  1.00000
##
## $12
## 12
##          n      mean      se      lcl      ucl      median
## estimate  500  4.98609 0.04169  4.90438 5.06779  4.95851
## SE.estimate 500  0.90085 0.00430  0.89242 0.90929  0.90171
## lcl       500  3.51110 0.03398  3.44451 3.57770  3.48590
## ucl       500  7.08761 0.05006  6.98950 7.18572  7.08376
## RB        500 -0.00278 0.00834 -0.01912 0.01356 -0.00830
## RSE       500  0.18362 0.00076  0.18213 0.18511  0.18219
## COV       500  0.94800 0.00994  0.92852 0.96748  1.00000

```

Non-uniform possums

Code to illustrate the use of homogeneous and inhomogeneous density models.

```

## add covariates to builtin secr object possummask
## D1 is homogeneous density
## D2 is artificial SW - NE gradient in density

xy <- apply(possummask,1,sum) / 500
covariates(possummask)[, "D1"] <- 2
covariates(possummask)[, "D2"] <- xy - mean(xy) + 2.5

## Note that this object already had a covariates dataframe
## -- if it didn't we would use
## covariates(possummask) <- data.frame ( D1 = ..., D2 = ...)

## specify scenarios
## anticipate two different sets of arguments for sim.poph
## with popindex = 1:2

scen6 <- make.scenarios (g0 = 0.2, sigma = 45, noccasions = 5,
  popindex = 1:2)

## specify alternate models for distribution of animals

poplist <- list(list(model2D = "IHP", D = "D1"),
  list(model2D = "IHP", D = "D2"))

## run scenarios and summarise
## we use the trap layout from the builtin secr object possumCH

sims6 <- run.scenarios (500, scen6, traps(possumCH), possummask,
  pop.args = poplist)

## Completed scenario 1
## Completed scenario 2
## Completed in 2.961 minutes

summary(sims6)

## run.scenarios(nrepl = 500, scenarios = scen6, trapset = traps(possumCH),
##   maskset = possummask, pop.args = poplist)
##
## Replicates      500
## Started         18:52:05 01 Dec 2017
## Run time        2.961 minutes
## Output class    selectedstatistics
##
## $constant
##           value
## trapsindex      1
## noccasions       5
## nrepeats         1
## g0               0.2
## sigma            45
## detectfn         0
## recapfactor      1

```

```

## detindex      1
## fitindex      1
## maskindex     1
##
## $varying
##   scenario    D popindex
##         1 2.0      1
##         2 2.5      2
##
## $detectors
##   trapsindex trapsname
##         1     traps1
##
## $pop.args
##   popindex model2D  D
##         1      IHP D1
##         2      IHP D2
##
## OUTPUT
##
## $1
##   1
##           n      mean      se
## n      500 111.86600 0.46103
## ndet  500 272.89200 1.12915
## nmov  500 143.05000 0.67248
## dpa   500   2.18628 0.00429
## rse   500   0.12355 0.00025
##
## $2
##   2
##           n      mean      se
## n      500 139.70400 0.48521
## ndet  500 330.40400 1.12189
## nmov  500 169.37400 0.68597
## dpa   500   2.12850 0.00358
## rse   500   0.11166 0.00019

```

To visualize individual realisations of the distribution of animals, use `fit = FALSE` (the default), `det.args = list(savepopn = TRUE)`, and save the entire capthist object (`extractfn = identity`). Here we create a single replicate.

```

sims6a <- run.scenarios (1, scen6, traps(possumCH), possummask,
  pop.args = poplist, det.args = list(savepopn = TRUE),
  extractfn = identity)

```


```

## Warning in if (detector(traps) %in% c("single", "multi")) {: the condition has length
## > 1 and only the first element will be used
## Completed scenario 1
## Warning in if (detector(traps) %in% c("single", "multi")) {: the condition has length
## > 1 and only the first element will be used
## Completed scenario 2
## Completed in 0.007 minutes

```

```
## sims6a$output is now a list (one component per scenario) of lists
## (one component per replicate) of simulated capthist objects, each
## with its 'popn' object embedded as an attribute

pop1 <- attr(sims6a$output[[1]][[1]], "popn")
pop2 <- attr(sims6a$output[[2]][[1]], "popn")
par(mfrow = c(1,2), mar=c(1,1,1,6))
plot(possummask, covariate = "D1", dots = FALSE, breaks = 0:6)
plot(traps(possumCH), detpar = list(col = 'green', pch = 15), add = TRUE)
plot(pop1, frame = FALSE, add = TRUE, col = "blue", pch = 16, cex = 0.6)
plot(possummask, covariate = 'D2', dots = FALSE, breaks = 0:6)
plot(traps(possumCH), detpar = list(col = 'green', pch = 15), add = TRUE)
plot(pop2, frame = FALSE, add = TRUE, col = "blue", pch = 16, cex = 0.6)
```



```
## click on map to display height; Esc to exit
spotHeight(possummask, prefix = "D2")
```

Fig. 6. Simulated homogeneous (left) and inhomogeneous (right) distributions of brushtail possums at Waitare, New Zealand. Traps in green (each hollow grid 180 m square).

Code for linear habitat

Code to illustrate the use of linear habitat models. This assumes you have the package **seclinear**. Some warnings and messages are suppressed.

```
library(seclinear)

## create a habitat geometry
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
linmask <- read.linearmask(data = xy, spacing = 5)

## define two possible detector layouts
trp1 <- make.line(linmask, detector = 'proximity', n = 80,
                  startbuffer = 200, endbuffer = 200, by = 30)
trp2 <- make.line(linmask, detector = 'proximity', n = 40,
```

```

        startbuffer = 200, endbuffer = 200, by = 60)
trplist <- list(spacing30 = trp1, spacing60 = trp2)

## create a scenarios dataframe
scen7 <- make.scenarios(D = c(50,200), trapsindex = 1:2,
                      sigma = 25, g0 = 0.2)

## we specify a mask, rather than construct it 'on the fly',
## and must manually add column 'maskindex' to the scenarios
scen7$maskindex <- c(1,1)

## we will use a non-Euclidean distance function...
det.arg <- list(userdist = networkdistance)

## run the scenarios and summarise results
sims7 <- run.scenarios(nrepl = 500, trapset = trplist,
                     maskset = linmask, det.args = list(det.arg),
                     scenarios = scen7, seed = 345, fit = FALSE)

## Completed scenario 1
## Completed scenario 2
## Completed scenario 3
## Completed scenario 4
## Completed in 2.384 minutes

summary(sims7)

## run.scenarios(nrepl = 500, scenarios = scen7, trapset = trplist,
##   maskset = linmask, det.args = list(det.arg), fit = FALSE,
##   seed = 345)
##
## Replicates      500
## Started         18:55:04 01 Dec 2017
## Run time        2.384 minutes
## Output class    selectedstatistics
##
## $constant
##           value
## nooccasions      3
## nrepeats         1
## g0               0.2
## sigma            25
## detectfn         0
## recapfactor      1
## popindex         1
## detindex         1
## fitindex         1
## maskindex        1
##
## $varying
##   scenario trapsindex  D
##         1         1  50

```

```

##          2          2  50
##          3          1 200
##          4          2 200
##
## $detectors
##   trapsindex trapsname
##           1 spacing30
##           2 spacing60
##
## $det.args
##   detindex   userdist
##           1 userdistfn
##
## OUTPUT
##
## $1
##   1
##           n          mean          se
## n      500  90.89600  0.40609
## ndet  500 152.00400  0.78590
## nmov   500  46.61200  0.38376
## dpa    500   1.44977  0.00294
## rse    500   0.16683  0.00050
##
## $2
##   2
##           n          mean          se
## n      500  59.17200  0.34544
## ndet  500  75.11200  0.46533
## nmov   500   6.58000  0.12055
## dpa    500   1.10159  0.00174
## rse    500   0.28971  0.00164
##
## $3
##   3
##           n          mean          se
## n      500 357.76000  0.84627
## ndet  500 600.05000  1.58310
## nmov   500 185.14600  0.76737
## dpa    500   1.45224  0.00144
## rse    500   0.08338  0.00012
##
## $4
##   4
##           n          mean          se
## n      500 236.1240  0.67737
## ndet  500 300.3580  0.93013
## nmov   500  26.6360  0.25583
## dpa    500   1.1024  0.00090
## rse    500   0.1417  0.00039

```

Grouped populations

This example demonstrates the simulation of a structured population - nominally females and males with a 2:1 sex ratio.

First we form a scenarios dataframe with 2 groups and two levels of ‘noccasions’, and manually adjust the ‘male’ parameter values:

```
scen8 <- make.scenarios (D = 8, g0 = 0.3, sigma = 30, noccasions = c(4,8),
                        groups = c('F','M'))
male <- scen8$group == 'M'
scen8$D[male] <- 4
scen8$g0[male] <- 0.2
scen8$sigma[male] <- 40
scen8[,1:8]
```

```
##  scenario group trapsindex noccasions nrepeats D  g0 sigma
## 1         1     F          1          4      1 8 0.3   30
## 2         1     M          1          4      1 4 0.2   40
## 3         2     F          1          8      1 8 0.3   30
## 4         2     M          1          8      1 4 0.2   40
```

Next we set up a trapping grid, a habitat mask, and a customized extract function for multi-class output from a hybrid mixture model:

```
grid <- make.grid(8, 8, spacing = 30)
mask <- make.mask(grid, buffer = 160, type = 'trapbuffer')
## extracts total density and proportion from output for the first group (F)
exfn <- function(x) {
  if (inherits(x, 'secl') & !is.null(x$fit)) {
    pred <- predict(x)
    pred[[1]][c('D','pmix'),]
  }
  else data.frame()
}
```

It is desirable to check the raw simulations. We specify the mask, rather than relying on one constructed automatically, to ensure the same mask is used for both females and males.

```
raw8 <- run.scenarios(20, scen8, trapset = list(grid), fit = FALSE, maskset = list(mask))
```

```
## Completed scenario 1
```

```
## Completed scenario 2
```

```
## Completed in 0.065 minutes
```

```
summary(raw8)
```

```
## run.scenarios(nrepl = 20, scenarios = scen8, trapset = list(grid),
##   maskset = list(mask), fit = FALSE)
##
## Replicates      20
## Started         18:57:27 01 Dec 2017
## Run time        0.065 minutes
## Output class    selectedstatistics
##
## $constant
##           value
```

```

## trapsindex      1
## nrepeats        1
## detectfn        0
## recapfactor     1
## popindex        1
## detindex        1
## fitindex        1
## maskindex       1
##
## $varying
##   scenario group noccasions D  g0 sigma
##         1    F         4 8 0.3   30
##         1    M         4 4 0.2   40
##         2    F         8 8 0.3   30
##         2    M         8 4 0.2   40
##
## $detectors
##   trapsindex trapsname
##           1   traps1
##
## OUTPUT
##
## $1
##   1
##           n      mean      se
## F.n      20  75.20000 1.36034
## F.ndet    20 190.25000 3.88037
## F.nmov    20  99.45000 2.54277
## F.dpa     20   2.22321 0.02309
## F.rse     20   0.14883 0.00141
## M.n       20  46.85000 1.36358
## M.ndet    20 118.20000 3.97995
## M.nmov    20  65.80000 2.65924
## M.dpa     20   2.35099 0.03109
## M.rse     20   0.18951 0.00290
##
## $2
##   2
##           n      mean      se
## F.n      20  87.45000 2.67392
## F.ndet    20 401.20000 12.42379
## F.nmov    20 270.85000 9.20505
## F.dpa     20   3.48190 0.04598
## F.rse     20   0.12183 0.00202
## M.n       20  53.25000 1.38007
## M.ndet    20 226.80000 7.18646
## M.nmov    20 158.30000 5.61253
## M.dpa     20   3.55734 0.05052
## M.rse     20   0.15756 0.00210

```

Now fit the models...

```

sims8 <- run.scenarios(20, scen8, trapset = list(grid), fit = TRUE, extractfn = exfn,
  fit.args = list(model = list(g0~h2, sigma~h2), hcov = 'group'),
  maskset = list(mask), ncores = 4, byscenario = FALSE)

```



```
## Completed scenario 1
```

```
## Completed scenario 2
```

```
## Completed in 18.195 minutes
```

... and check the summary output for density ('D') and sex ratio (proportion female 'pmix') without repeating the header information:

```
summary(select.stats(sims8,'D'))$OUTPUT
```

```
## $`1`
```

```
##           n      mean      se
## estimate  20 11.63774 0.23427
## SE.estimate 20  1.14811 0.01201
## lcl       20  9.59652 0.21187
## ucl       20 14.11414 0.25702
## RB        20 -0.03019 0.01952
## RSE       20  0.09901 0.00097
## COV       20  0.95000 0.05000
##
```

```
## $`2`
```

```
##           n      mean      se
## estimate  20 11.64039 0.23081
## SE.estimate 20  1.04109 0.01184
## lcl       20  9.77242 0.20890
## ucl       20 13.86615 0.25358
## RB        20 -0.02997 0.01923
## RSE       20  0.08975 0.00088
## COV       20  0.95000 0.05000
##
```

```
summary(select.stats(sims8,'pmix'))$OUTPUT
```

```
## $`1`
```

```
##           n      mean      se
## estimate  20 0.68365 0.00725
## SE.estimate 20 0.04533 0.00063
## lcl       20 0.58899 0.00799
## ucl       20 0.76520 0.00617
## RB        0      NA      NA
## RSE       20 0.06659 0.00152
## COV       0      NA      NA
##
```

```
## $`2`
```

```
##           n      mean      se
## estimate  20 0.67844 0.00958
## SE.estimate 20 0.04042 0.00062
## lcl       20 0.59468 0.01030
## ucl       20 0.75208 0.00846
## RB        0      NA      NA
## RSE       20 0.05999 0.00163
## COV       0      NA      NA
```