

index.G3(clusterSim)

### G3 Hubert & Levine internal cluster quality index

$$G3(u) = \frac{D(u) - r \cdot D_{\min}}{r \cdot D_{\max} - r \cdot D_{\min}}, \quad D_{\min} \neq D_{\max},$$
$$G3(u) \in (0, 1),$$

where:  $D(u)$  – all within-cluster dissimilarities,

$r$  – number of within-cluster dissimilarities,

$D_{\min}$  – smallest within-cluster dissimilarity,

$D_{\max}$  – largest within-cluster dissimilarity,

$u$  – number of clusters ( $u = 2, \dots, n - 2$ ).

The value of  $u$ , which minimizes  $G3(u)$ , is regarded as specifying the number of clusters.

### References

- Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wrocław, p. 339.
- Gordon, A.D. (1999), *Classification*, Chapman & Hall/CRC, London, p. 62.
- Milligan, G.W., Cooper, M.C. (1985), *An examination of procedures of determining the number of cluster in a data set*, "Psychometrika", vol. 50, no. 2, pp. 159-179.