

Package ‘d3po’

June 19, 2023

Type Package

Title Fast and Beautiful Interactive Visualization for 'Markdown' and 'Shiny'

Version 0.5.5

Description Apache licensed alternative to 'Highcharter' which provides functions for both fast and beautiful interactive visualization for 'Markdown' and 'Shiny'.

Depends htmlwidgets, magrittr, R (>= 2.10)

URL <https://pacha.dev/d3po/>

BugReports <https://github.com/pachadotdev/d3po/issues>

License Apache License (>= 2.0)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

NeedsCompilation no

Imports assertthat, dplyr, purrr, rlang

Suggests knitr, igrph, rmarkdown, shiny, golem

VignetteBuilder knitr

Author Mauricio Vargas Sepulveda [aut, cre, cph],
John Coene [aut],
Riva Quiroga [ctb],
Ariel Alvarado [ctb],
Sylvain Lesage [ctb],
Curran Kelleher [ctb],
Fernando Becerra [ctb],
Natural Earth [dct],
R Consortium [fnd]

Maintainer Mauricio Vargas Sepulveda <m.sepulveda@mail.utoronto.ca>

Repository CRAN

Date/Publication 2023-06-19 08:10:02 UTC

R topics documented:

| | |
|-----------------|-----------|
| d3po | 2 |
| d3po-exports | 3 |
| d3po-shiny | 3 |
| d3po_template | 4 |
| daes | 4 |
| maps | 5 |
| map_ids | 5 |
| pokemon | 6 |
| pokemon_network | 7 |
| po_area | 7 |
| po_background | 8 |
| po_bar | 9 |
| po_box | 10 |
| po_donut | 10 |
| po_font | 11 |
| po_geomap | 12 |
| po_labels | 13 |
| po_legend | 13 |
| po_line | 14 |
| po_network | 15 |
| po_pie | 15 |
| po_scatter | 16 |
| po_title | 18 |
| po_treemap | 18 |
| Index | 20 |

d3po

An htmlwidget interface to the d3po javascript chart library

Description

This function provides 'd3po' methods from R console

Usage

```
d3po(data = NULL, ..., width = NULL, height = NULL, elementId = NULL)
```

Arguments

| | |
|-------|--|
| data | d3po need explicit specified data objects formatted as JSON, and this parameter passed it from R. |
| ... | Aesthetics to pass, see daes() |
| width | Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended. |

| | |
|-----------|---|
| height | Same as width parameter. |
| elementId | Dummy string parameter. Useful when you have two or more charts on the same page. |

Value

Creates a basic 'htmlwidget' object for simple visualization

Author(s)

Mauricio Vargas

| | |
|--------------|----------------------------------|
| d3po-exports | <i>D3po (re)exported methods</i> |
|--------------|----------------------------------|

Description

D3po (re)exported methods

| | |
|------------|----------------------------------|
| d3po-shiny | <i>Shiny bindings for 'd3po'</i> |
|------------|----------------------------------|

Description

Output and render functions for using d3po within Shiny applications and interactive Rmd documents.

Usage

```
d3po_output(output_id, width = "100%", height = "400px")

render_d3po(expr, env = parent.frame(), quoted = FALSE)

d3po_proxy(id, session = shiny::getDefaultReactiveDomain())
```

Arguments

| | |
|---------------|--|
| output_id | output variable to read from |
| width, height | Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended. |
| expr | An expression that generates a d3po object |
| env | The environment in which to evaluate expr. |
| quoted | Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable. |
| id | Id of plot to create a proxy of. |
| session | A valid shiny session. |

Value

Creates a basic 'htmlwidget' object for 'Shiny' and interactive documents

| | |
|---------------|--|
| d3po_template | <i>Create a new d3po templated project</i> |
|---------------|--|

Description

Create a new d3po templated project

Usage

```
d3po_template(path)
```

Arguments

| | |
|------|---------------------------------------|
| path | The path to create the new project in |
|------|---------------------------------------|

| | |
|------|-------------------|
| daes | <i>Aesthetics</i> |
|------|-------------------|

Description

Aesthetics of the chart.

Usage

```
daes(x, y, ...)
```

Arguments

| | |
|-----------|---|
| x, y, ... | List of name value pairs giving aesthetics to map to variables. The names for x and y aesthetics are typically omitted because they are so common; all other aspects must be named. |
|-----------|---|

Value

Aesthetics for the plots such as axis (x,y), group, color and/or size

Aesthetics

Valid aesthetics (depending on the geom)

- x, y: cartesian coordinates.
- group: grouping data.
- color: color of geom.
- size: size of geom.
- layout: layout of geom (nicely, fr, kk, graphopt, drl, lgl, mds, sugiyama), in quotes.

maps

maps

Description

World, continent and country maps. These maps are provided as R lists structured by following the 'topojson' standard. The maps are organized in sub-lists by continent and here I provide maps for both the continents and the countries. There are missing states or regions because those could not be found in the original maps.

Usage

maps

Format

A list object with 6 elements (one per continent). The Americas are separated in North America and South America.

Details

Missing in Asia: 'Siachen Glacier (JK)', 'Scarborough Reef (SH)', and 'Spratly Islands (SP)'.
Missing in Europe: 'Vatican City (VA)'.

Missing in North America: 'Bajo Nuevo Bank (BU)', 'Serranilla Bank (SW)', and 'United States Minor Outlying Islands (UM)'.

Missing in Oceania: 'Federated States of Micronesia (FM)', 'Marshall Islands (MH)', and 'Tuvalu (TV)'.

Consider all these maps as referential and unofficial.

Source

Adapted from Natural Earth.

map_ids

Extract the IDs from a Map

Description

Extract the IDs from a Map

Usage

map_ids(map)

Arguments

map A map object

Value

A tibble containing IDs and names

Examples

```
map <- map_ids(maps$south_america$continent)
```

| | |
|---------|----------------|
| pokemon | <i>pokemon</i> |
|---------|----------------|

Description

Statistical information about 151 Pokemon from Nintendo RPG series.

Usage

```
pokemon
```

Format

A data frame with 151 observations and 15 variables.

Variables

- id: Pokedex number.
- name: Pokedex name.
- height: Height in meters.
- weight: Weight in kilograms.
- base_experience: How much the Pokemon has battled.
- type_1: Primary Pokemon type (i.e. Grass, Fire and Water)
- type_2: Secondary Pokemon type (i.e. Poison, Dragon and Ice)
- attack: How much damage a Pokemon deals when using a technique.
- defense: How much damage a Pokemon receives when it is hit by a technique.
- hp: How much damage a Pokemon can receive before fainting.
- special_attack: How much damage a Pokemon deals when using a special technique.
- special_defense: How much damage a Pokemon receives when it is hit by a special technique.
- speed: Determines the order of Pokemon that can act in battle, if the speed is tied then the 1st move is assigned at random.
- color_1: Hex color code for Type 1.
- color_2: Hex color code for Type 2.

Source

Adapted from highcharter package.

| | |
|-----------------|------------------------|
| pokemon_network | <i>pokemon_network</i> |
|-----------------|------------------------|

Description

Connections between Pokemon types based on Type 1 and 2.

Usage

```
pokemon_network
```

Format

A igraph object with 17 vertices (nodes) and 26 edges (arcs).

Source

Adapted from the highcharter package.

| | |
|---------|-------------|
| po_area | <i>Area</i> |
|---------|-------------|

Description

Plot an area chart.

Usage

```
po_area(d3po, ..., data = NULL, inherit_daes = TRUE, stack = FALSE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| inherit_daes | Whether to inherit aesthetics previous specified. |
| stack | Whether to stack the series. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
# library(dplyr)
# dout <- pokemon %>%
#   filter(
#     type_1 == "water"
#   ) %>%
#   group_by(type_1, color_1) %>%
#   reframe(
#     probability = c(0, 0.25, 0.5, 0.75, 1),
#     quantile = quantile(speed, probability)
#   )

dout <- data.frame(
  type_1 = rep("water", 5),
  color_1 = rep("#6890F0", 5),
  probability = c(0, 0.25, 0.5, 0.75, 1),
  quantile = c(15, 57.25, 70, 82, 115)
)

d3po(dout) %>%
  po_area(daes(
    x = probability, y = quantile, group = type_1,
    color = color_1
  )) %>%
  po_title("Sample Quantiles for Water Pokemon Speed")
```

po_background

Background

Description

Add a background to a chart.

Usage

```
po_background(d3po, background = "#fff")
```

Arguments

d3po Either the output of `d3po()` or `d3po_proxy()`.
background background to add (hex code).

Value

Appends custom background to an 'htmlwidgets' object

| | |
|--------|------------|
| po_bar | <i>Bar</i> |
|--------|------------|

Description

Draw a bar chart.

Usage

```
po_bar(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
# library(dplyr)
# dout <- pokemon %>%
#   group_by(type_1, color_1) %>%
#   count()

dout <- data.frame(
  type_1 = c(
    "bug", "dragon", "electric", "fairy", "fighting",
    "fire", "ghost", "grass", "ground", "ice",
    "normal", "poison", "psychic", "rock", "water"
  ),
  color_1 = c(
    "#A8B820", "#7038F8", "#F8D030", "#EE99AC", "#C03028",
    "#F08030", "#705898", "#78C850", "#E0C068", "#98D8D8",
    "#A8A878", "#A040A0", "#F85888", "#B8A038", "#6890F0"
  ),
  n = c(
    12, 3, 9, 2, 7,
    12, 3, 12, 8, 2,
    22, 14, 8, 9, 28
  )
)

d3po(dout) %>%
  po_bar(daes(x = type_1, y = n, color = color_1)) %>%
  po_title("Share of Pokemon by main type")
```

| | |
|--------|----------------|
| po_box | <i>Boxplot</i> |
|--------|----------------|

Description

Draw a boxplot.

Usage

```
po_box(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
d3po(pokemon) %>%
  po_box(daes(x = type_1, y = speed, color = color_1)) %>%
  po_title("Distribution of Pokemon speed by main type")
```

| | |
|----------|--------------|
| po_donut | <i>Donut</i> |
|----------|--------------|

Description

Plot a donut

Usage

```
po_donut(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
# library(dplyr)
# dout <- pokemon %>%
#   group_by(type_1, color_1) %>%
#   count()

dout <- data.frame(
  type_1 = c(
    "bug", "dragon", "electric", "fairy", "fighting",
    "fire", "ghost", "grass", "ground", "ice",
    "normal", "poison", "psychic", "rock", "water"
  ),
  color_1 = c(
    "#A8B820", "#7038F8", "#F8D030", "#EE99AC", "#C03028",
    "#F08030", "#705898", "#78C850", "#E0C068", "#98D8D8",
    "#A8A878", "#A040A0", "#F85888", "#B8A038", "#6890F0"
  ),
  n = c(
    12, 3, 9, 2, 7,
    12, 3, 12, 8, 2,
    22, 14, 8, 9, 28
  )
)

d3po(dout) %>%
  po_donut(daes(size = n, group = type_1, color = color_1)) %>%
  po_title("Share of Pokemon by main type")
```

po_font

Font

Description

Edit the font used in a chart.

Usage

```
po_font(d3po, family = "Fira Sans", size = 16, transform = "none")
```

Arguments

| | |
|-----------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| family | family font to use ("Roboto", "Merriweather", etc.). |
| size | size to use (10, 11, 12, etc. overrides auto-sizing). |
| transform | transformation to use for the title ("lowercase", "uppercase", "capitalize", "none"). |

Value

Appends custom font to an 'htmlwidgets' object

po_geomap

Geomap

Description

Plot a geomap

Usage

```
po_geomap(d3po, ..., data = NULL, map = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| map | map to use (i.e., any valid list or topojson file such as <code>maps\$south_america</code> or <code>jsonlite::fromJSON("south_america.topojson", simplifyVector = F)</code>) |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
dout <- map_ids(d3po::maps$asia$japan)
dout$value <- ifelse(dout$id == "TK", 1L, NA)
dout$color <- ifelse(dout$id == "TK", "#bd0029", NA)

d3po(dout) %>%
  po_geomap(
    daes(
      group = id, color = color, size = value,
      tooltip = name
    ),
    map = d3po::maps$asia$japan
  ) %>%
  po_title("Pokemon was created in the Japanese city of Tokyo")
```

| | |
|-----------|---------------|
| po_labels | <i>Labels</i> |
|-----------|---------------|

Description

Edit labels positioning in a chart.

Usage

```
po_labels(d3po, align = "center", valign = "middle", resize = TRUE)
```

Arguments

| | |
|--------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| align | horizontal alignment ("left", "center", "right", "start", "middle", "end"). |
| valign | vertical alignment ("top", "middle", "bottom"). |
| resize | resize labels text (TRUE or FALSE). |

Value

Appends custom labels to an 'htmlwidgets' object

| | |
|-----------|---------------|
| po_legend | <i>Legend</i> |
|-----------|---------------|

Description

Add a legend to a chart.

Usage

```
po_legend(d3po, legend)
```

Arguments

| | |
|--------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| legend | legend to add. |

Value

Appends custom legend to an 'htmlwidgets' object

| | |
|---------|-------------|
| po_line | <i>Line</i> |
|---------|-------------|

Description

Plot an line chart.

Usage

```
po_line(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
# library(dplyr)
# dout <- pokemon %>%
#   filter(
#     type_1 == "water"
#   ) %>%
#   group_by(type_1, color_1) %>%
#   reframe(
#     probability = c(0, 0.25, 0.5, 0.75, 1),
#     quantile = quantile(speed, probability)
#   )

dout <- data.frame(
  type_1 = rep("water", 5),
  color_1 = rep("#6890F0", 5),
  probability = c(0, 0.25, 0.5, 0.75, 1),
  quantile = c(15, 57.25, 70, 82, 115)
)

d3po(dout) %>%
  po_line(daes(
    x = probability, y = quantile, group = type_1,
    color = color_1
  )) %>%
  po_title("Sample Quantiles for Water Pokemon Speed")
```

| | |
|------------|----------------|
| po_network | <i>Network</i> |
|------------|----------------|

Description

Draw a network.

Usage

```
po_network(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|--|
| d3po | Either the output of d3po() or d3po_proxy() . |
| ... | Aesthetics, see daes() . |
| data | Any dataset to use for plot, overrides data passed to d3po() . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

Appends nodes arguments to a network-specific 'htmlwidgets' object

Examples

```
d3po(pokemon_network) %>%
  po_network(daes(size = size, color = color, layout = "kk")) %>%
  po_title("Connections Between Pokemon Types")
```

| | |
|--------|------------|
| po_pie | <i>Pie</i> |
|--------|------------|

Description

Plot a pie

Usage

```
po_pie(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|--|
| d3po | Either the output of d3po() or d3po_proxy() . |
| ... | Aesthetics, see daes() . |
| data | Any dataset to use for plot, overrides data passed to d3po() . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
# library(dplyr)
# dout <- pokemon %>%
#   group_by(type_1, color_1) %>%
#   count()

dout <- data.frame(
  type_1 = c(
    "bug", "dragon", "electric", "fairy", "fighting",
    "fire", "ghost", "grass", "ground", "ice",
    "normal", "poison", "psychic", "rock", "water"
  ),
  color_1 = c(
    "#A8B820", "#7038F8", "#F8D030", "#EE99AC", "#C03028",
    "#F08030", "#705898", "#78C850", "#E0C068", "#98D8D8",
    "#A8A878", "#A040A0", "#F85888", "#B8A038", "#6890F0"
  ),
  n = c(
    12, 3, 9, 2, 7,
    12, 3, 12, 8, 2,
    22, 14, 8, 9, 28
  )
)

d3po(dout) %>%
  po_pie(daes(size = n, group = type_1, color = color_1)) %>%
  po_title("Share of Pokemon by main type")
```

po_scatter

scatter

Description

Plot an scatter chart.

Usage

```
po_scatter(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
# library(dplyr)
# dout <- pokemon %>%
#   group_by(type_1, color_1) %>%
#   summarise(
#     attack = mean(attack),
#     defense = mean(defense)
#   ) %>%
#   mutate(log_attack_x_defense = log(attack * defense))

dout <- data.frame(
  type_1 = c(
    "bug", "dragon", "electric", "fairy", "fighting",
    "fire", "ghost", "grass", "ground", "ice",
    "normal", "poison", "psychic", "rock", "water"
  ),
  color_1 = c(
    "#A8B820", "#7038F8", "#F8D030", "#EE99AC", "#C03028",
    "#F08030", "#705898", "#78C850", "#E0C068", "#98D8D8",
    "#A8A878", "#A040A0", "#F85888", "#B8A038", "#6890F0"
  ),
  attack = c(
    63.7, 94, 62, 57.5, 102.8,
    83.9, 50, 70.6, 81.8, 67.5,
    67.7, 74.4, 60.1, 82.2, 70.2
  ),
  defense = c(
    57, 68.3, 64.6, 60.5, 61,
    62.5, 45, 69.5, 86.2, 67.5,
    53.5, 67, 57.5, 110, 77.5
  ),
  log_attack_x_defense = c(
    8.1, 8.7, 8.2, 8.1, 8.7,
    8.5, 7.7, 8.5, 8.8, 8.4,
    8.1, 8.5, 8.1, 9.1, 8.6
  )
)

d3po(dout) %>%
  po_scatter(daes(
    x = defense, y = attack,
    size = log_attack_x_defense, group = type_1, color = color_1
  )) %>%
  po_title("Pokemon Mean Attack vs Mean Defense by Main Type")
```

| | |
|----------|--------------|
| po_title | <i>Title</i> |
|----------|--------------|

Description

Add a title to a chart.

Usage

```
po_title(d3po, title)
```

Arguments

| | |
|-------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| title | Title to add. |

Value

Appends a title to an 'htmlwidgets' object

| | |
|------------|----------------|
| po_treemap | <i>Treemap</i> |
|------------|----------------|

Description

Plot a treemap

Usage

```
po_treemap(d3po, ..., data = NULL, inherit_daes = TRUE)
```

Arguments

| | |
|--------------|---|
| d3po | Either the output of <code>d3po()</code> or <code>d3po_proxy()</code> . |
| ... | Aesthetics, see <code>daes()</code> . |
| data | Any dataset to use for plot, overrides data passed to <code>d3po()</code> . |
| inherit_daes | Whether to inherit aesthetics previous specified. |

Value

an 'htmlwidgets' object with the desired interactive plot

Examples

```
# library(dplyr)
# dout <- pokemon %>%
#   group_by(type_1, color_1) %>%
#   count()

dout <- data.frame(
  type_1 = c(
    "bug", "dragon", "electric", "fairy", "fighting",
    "fire", "ghost", "grass", "ground", "ice",
    "normal", "poison", "psychic", "rock", "water"
  ),
  color_1 = c(
    "#A8B820", "#7038F8", "#F8D030", "#EE99AC", "#C03028",
    "#F08030", "#705898", "#78C850", "#E0C068", "#98D8D8",
    "#A8A878", "#A040A0", "#F85888", "#B8A038", "#6890F0"
  ),
  n = c(
    12, 3, 9, 2, 7,
    12, 3, 12, 8, 2,
    22, 14, 8, 9, 28
  )
)

d3po(dout) %>%
  po_treemap(daes(size = n, group = type_1, color = color_1)) %>%
  po_title("Share of Pokemon by main type")
```

Index

* datasets

- maps, [5](#)
- pokemon, [6](#)
- pokemon_network, [7](#)
- %>% (d3po-exports), [3](#)

- d3po, [2](#)
- d3po(), [7–16, 18](#)
- d3po-exports, [3](#)
- d3po-shiny, [3](#)
- d3po_output (d3po-shiny), [3](#)
- d3po_proxy (d3po-shiny), [3](#)
- d3po_proxy(), [7–16, 18](#)
- d3po_template, [4](#)
- daes, [4](#)
- daes(), [2, 7, 9, 10, 12, 14–16, 18](#)

- JS (d3po-exports), [3](#)

- map_ids, [5](#)
- maps, [5](#)

- po_area, [7](#)
- po_background, [8](#)
- po_bar, [9](#)
- po_box, [10](#)
- po_donut, [10](#)
- po_font, [11](#)
- po_geomap, [12](#)
- po_labels, [13](#)
- po_legend, [13](#)
- po_line, [14](#)
- po_network, [15](#)
- po_pie, [15](#)
- po_scatter, [16](#)
- po_title, [18](#)
- po_treemap, [18](#)
- pokemon, [6](#)
- pokemon_network, [7](#)

- render_d3po (d3po-shiny), [3](#)