

Package ‘tabularmaps’

October 14, 2022

Title Create Tile-Grid Geographical Maps

Version 0.1.0

Description The ‘tabularmap’ is one of the visualization methods for efficiently displaying data consisting of multiple elements by tiling them. When dealing with geospatial, it corrects for differences in visibility between areas.

License CC BY-SA 4.0

URL <https://github.com/uribo/tabularmaps>

BugReports <https://github.com/uribo/tabularmaps/issues>

Depends R (>= 3.3.0)

Imports ggforce (>= 0.3.2), ggplot2 (>= 3.3.0), purrr (>= 0.3.4), rlang (>= 0.4.7)

Suggests countrycode, zipangu, knitr, rmarkdown, testthat (>= 2.1.0)

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Shinya Uryu [aut, cre] (<<https://orcid.org/0000-0002-0493-6186>>)

Maintainer Shinya Uryu <suika1127@gmail.com>

Repository CRAN

Date/Publication 2020-08-04 09:00:02 UTC

R topics documented:

iso3166	2
jpn77	2
scale_fill_jpregion	3
tabularmap	3
theme_tabularmap	5
tky23	5

Index**6**

iso3166*Country list*

Description

A data frame include ISO-3166 codes.

Usage

```
iso3166
```

Format

A data frame with 250 rows 8 variables:

- country_name:
- continent:
- region:
- iso2c:
- iso3c:
- iso3n: 3 digits number (as character)
- x: Coordinates for displaying as tabularmap
- y: Coordinates for displaying as tabularmap

jpn77*Japan 7x7 grid dataset*

Description

Prefectures dataset.

Usage

```
jpn77
```

Format

A data frame with 47 rows 8 variables:

- jis_code: jis code
- prefecture: prefecture names
- region: region
- major_island:
- prefecture_kanji:
- region_kanji:
- x: Coordinates for displaying as tabularmap
- y: Coordinates for displaying as tabularmap

scale_fill_jpregion *Coloring the tabularmaps by region in Japan*

Description

Custom ggplot2 scale for tabulamap.

Usage

```
scale_fill_jpregion(lang, ...)
```

Arguments

lang	Select whether the region variable is Japanese (jp) or English (en).
...	all other arguments passed on to ggplot2::scale_fill_manual()

tabularmap *Create Tile-Grid*

Description

A ggplot2-based tabularmap that places a coordinated dataset in a rectangle.

Usage

```
tabularmap(
  data,
  x,
  y,
  group,
  fill = NULL,
  label = NULL,
  ...,
  .expand_size = 10,
  .radius_size = 2
)
```

Arguments

<code>data</code>	data.frame. Contain <code>x</code> , <code>y</code> , <code>group</code> and <code>label</code> variables used as coordinates.
<code>x</code> , <code>y</code>	A column containing the numbers to line up the items.
<code>group</code>	Group variable.
<code>fill</code>	Fill colour variable.
<code>label</code>	Label variable.
<code>...</code>	All other arguments passed on to <code>ggplot2::geom_text()</code> include label family.
<code>.expand_size</code>	The value specified in the expand argument of <code>ggforce::geom_shape()</code> . The unit is in mm.
<code>.radius_size</code>	The value specified in the radius argument of <code>ggforce::geom_shape()</code> . The unit is in pt.

Examples

```
library(ggplot2)
tabularmap(jpn77, x, y, group = jis_code, label = prefecture, size = 3)
tabularmap(jpn77, x, y, group = jis_code, fill = region, label = prefecture, size = 3) +
  theme_tabularmap() +
  scale_fill_jpregion(lang = "en")
tabularmap(data.frame(
  id = letters[seq.int(9)],
  x = rep(c(1,2,3), each = 3),
  y = rep(c(1,2,3), times = 3),
  fill = seq.int(9),
  label = letters[seq.int(9)]),
  x, y,
  group = id,
  fill = fill,
  label = label,
  .expand_size = 20, .radius_size = 10)
tabularmap(iso3166, x, y, group = iso2c,
  fill = continent,
  label = iso2c,
  .expand_size = 5) +
```

```
theme_tabularmap() +  
guides(fill = FALSE)
```

theme_tabularmap	<i>Tabularmap theme</i>
------------------	-------------------------

Description

Custom ggplot2 theme for tabulamap.

Usage

```
theme_tabularmap(...)
```

Arguments

...	all other arguments passed on to ggplot2::theme_minimal()
-----	---

tky23	<i>Special wards of Tokyo</i>
-------	-------------------------------

Description

Tokyo 23 wards dataset.

Usage

```
tky23
```

Format

A data frame with 23 rows 5 variables:

- no: Identical number
- ward: Name
- ward_kanji: Names in Kanji
- x, y: Coordinates for displaying as tabulamap

Index

```
* datasets
  iso3166, 2
  jpn77, 2
  tky23, 5

  ggforce::geom_shape(), 4
  ggplot2::geom_text(), 4
  ggplot2::scale_fill_manual(), 3
  ggplot2::theme_minimal(), 5

  iso3166, 2
  jpn77, 2
  scale_fill_jpregion, 3

  tabularmap, 3
  theme_tabularmap, 5
  tky23, 5
```